SAFETY DATA SHEET

Glass Cast

page 1/21

in acc. with Regulation (EU) No. 2015/830 Revision Date: 04/02/2019

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

SECTION 1: IDENTIFICATION OF SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1. Product identifier

Tradename: CULR™ Art Pigment for Epoxy – AshGrey

Chemical

characterisation: C.I. Pigment Red 101, Yellow 42, Black 26 and Calciumcarbonat in

aqueous dispersion, contenting Polyglykol and 1,2-Propandiol.

1.2. Relevant identified uses of the substance or mixture and uses advised again

Relevant identified uses of the substance or mixture:

Industry sector: Industrial Performance Chemicals

Paints, lacquers and varnishes industry

Polymers industry Printing Inks Industry

Type of use: Colourant preparation

1.3. Details of the supplier of the safety data sheet

Identification of the company:

Easy Composites Ltd

Unit 39 Park Hall Business Village

Stoke on Trent, ST3 5XA. United Kingdom.

Phone: +44 (0)1782 4544499

Information to substance / mixture:

Division: Technical

E-mail: technical@glasscastresin.com

1.4. Emergency telephone number

Emergency CONTACT (Office Hours) Phone: +44 (0)1782 4544499

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance / mixture

Classification according CLP regulation (Regulation (EC) No. 1272/2008, as amended):

Categoryof danger	Category HazardSymbol	H-Phrases

Not a hazardous substance or mixture.

2.2. Label elements

Labelling according CLP regulation (Regulation (EC) No. 1272/2008, as amended):

Not a hazardous substance or mixture.

Additional Labelling:

EUH 208 contains mixture of: 1,2-Benzisothiazol-3(2H)-one,

mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one(3:1).

and 2-methyl-2H-isothiazor-3-one(3.1)

May produce an allergic reaction.

EUH210: Safety data sheet available on request.

2.3. Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1 % or higher.

No hazards to be specially mentioned.

CULR[™] Art Pigment for Epoxy – Ash Grey Tradename: page 2/21

SECTION 3: COMPOSITION / INFORMATION TO INGREDIENTS

3.1. Mixtures

Hazardous ingredients:

Alcohols, C16-18 and C18-unsaturated, ethoxylated (8 EO)

Concentration: ≥ 3.0 - ≤ 6.8 % CAS-Number: 68920-66-1 EC-Number: 500-236-9

GHS classification EC:

Skin irritation	Category 2	H315
Acute aquatic toxicity	Category 1	H400
Chronic aquatic toxicity	Category 3	H412
M-Factor (Acute aquatic toxicity)		

M-Factor (Acute aquatic toxicity)

1,2-Benzisothiazolin-3-on

Concentration: ≥ 0,0025 - ≤ 0,025 %

CAS-Number: 2634-33-5 EC-Number: 220-120-9 INDEX-No.: 613-088-00-6 01-2120761540-60 Registrationnumber:

GHS classification EC:

Acute toxicity	Category 4	H302
Fatal ifinhaled	Category 2	H330
Skin irritation	Category 2	H315
May cause an alergic skin reaction	Category 1	H317
Serious eye damage	Category 1	H318
Acute aquatic toxicity	Category 1	H400
Chronic aquatic toxicity	Category 2	H411

Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one(3:1)

Concentration: ≥ 0,0002 - ≤ 0,0015 %

CAS-Number: 55965-84-9 EC-Number: 611-341-5 613-167-005 INDEX-No.: Registrationnumber: 01-2120764691-48

GHS classification EC:

Acute toxicity	Category 3	H301
Acute toxocity	Category 2	H310
Fatal ifinhaled	Category 2	H330
Causes severe skin burns and eye d.	Category 1B	H314
May cause an alergic skin reaction	Category 1	H317
Acute aquatic toxicity	Category 1	H400
Chronic aquatic toxicity	Category1	H410

The text of H-phrases is shown in section 16.

SECTION 4: FIRST AID MEASURES

4.1. Discription of first aid measures

General information:

Get medical advice/ attention if you feel unwell.

After inhalation:

Move the victim to fresh air.

If you feel unwell, seek medical advice (show the label where possible).

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

page 3/21

After contact with skin:

In case of contact with skin, clean with plenty of soap and water.

After contact with eyes:

In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion:

If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed symptoms

Symptoms:

None known.

Hazards:

None known.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet

Dry powder

Carbon dioxide (CO₂)

Alcohol resistant foam

Extinguishing media that must not be used for safety reasons:

High volume water jet

5.2. Special hazards arising from the substance or mixture

In case of fires, hazardous combustion gases are formed:

Carbon oxides (CO_x)

Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Special protective equipment for firefighting:

Use self-contained breathing apparatus.

Further information:

Wear suitable protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear suitable personal protective equipment.

6.2. Environment precautions

The product should not be allowed to enter drains, water courses or the soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Treat recovered material as described in the section "Disposal considerations".

6.4. Reference to other sections

Additional information:

Information regarding safe handling, see chapter 7.

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey page 4/21

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling:

When used and handled appropriately no special measures are needed.

Hygiene measures:

Wash hands before breaks and at the end of workday.

Use protective skin cream before handling the product.

Take off immediately all contaminated clothing and wash it before reuse.

Advice on protection against fire and explosion:

Normal measures for preventive fire protection.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions:

Keep containers tightly closed in a cool, well-ventilated place.

Handle and open container with care.

Keep away from flames and sparks.

Storage stability:

Minimum 36 months.

7.3. Specific end use(s)

No further recommendations.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Exposure limit values:

Exposure limit values are not available.

DNEL / DMEL-values:

Iron(III)-Oxide

EC-Number: 215-168-2 CAS-Number: 1309-37-1

Route of exposure	End use	Potential health effects	Value	Remarks
Inhalation	Workers	Long-term local effects	10 mg/m ³	DNEL, inhalable dust

manganese ferrite black spinel EC-Number: 269-056-3 CAS-Number: 68186-94-7

Route of exposure	End use	Potential health effects	Value	Remarks
Inhalation	Workers	Long-term local effects	10 mg/m ³	DNEL

C.I. Pigment Yellow 42 EC-Number: 257-098-5

CAS-Number: 51274-00-1

Route of exposure	End use	Potential health effects	Value	Remarks
Inhalation	Workers	Long-term local effects	10 mg/m ³	DNEL

page 5/21

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

1,2-Benzisothiazol-3(2H)-one EC-Number: 220-120-9 CAS-Number: 2634-33-5

Route of exposure	End use	Potential health effects	Value	Remarks
Inhalation	Workers	Long-term systemic effects	6,81 mg/m ³	DNEL
Dermal	Workers	Long-term systemic effects	0,966 mg/kg bw/day	DNEL
Inhalation	Consumers	Long-term systemic effects	1,2 mg/m ³	DNEL
Dermal	Consumers	Long-term systemic effects	0,345 mg/kg bw/day	DNEL

Amorphous silicon dioxide EC-Number: 231-545-4 CAS-Number: 7631-86-9

Route of exposure	End use	Potential health effects	Value	Remarks
Inhalation	Workers	Long-term local effects	4 mg/m ³	DNEL

Propylene Glycol

EC-Number: 200-338-0 CAS-Number: 57-55-6

Route of exposure	End use	Potential health effects	Value	Remarks
Inhalation	Workers	Long-term systemic effects	168 mg/m ³	DNEL
Inhalation	Workers	Long-term local effects	10 mg/m ³	DNEL
Inhalation	Consumers	Long-term systemic effects	50 mg/m ³	DNEL
Inhalation	Consumers	Long-term local effects	10 mg/m ³	DNEL
Skin contact	Consumers	Long-term systemic effects	213 mg/m ³	
Ingestion	Consumers	Long-term systemic effects	85 mg/m ³	

PNEC-values: Propylene Glycol

EC-Number: 200-338-0 CAS-Number: 57-55-6

Environmental compartment	Value
Fresh water	260 mg/l
Marine water	26 mg/l
Water (intermittent release)	183 mg/l
Sewage treatment plant	20000 mg/l
Fresh water sediment	572 mg/kg dry weight (d.w.)
Marine sediment	57,2 mg/kg dry weight (d.w.)
Soil	50 mg/kg dry weight (d.w.)

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

1,2-Benzisothiazol-3(2H)-one EC-Number: 220-120-9 CAS-Number: 2634-33-5

Environmental compartment	Value
Fresh water	0,00403 mg/l
Marine water	0,000403 mg/l
Intermittend use/release	0,0011 mg/l
Sewage treatment plant	1,03 mg/l
Fresh water sediment	0,0499 mg/kg dry weight (d.w.)
Marine sediment	0,00499 mg/kg dry weight (d.w.)
Soil	3 mg/kg dry weight (d.w.)

page 6/21

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

EC-Number: 611-341-5 CAS-Number: 55965-84-9

Environmental compartment	Value	
Fresh water	0,049 µg/l	
Marine water	0,0098 µg/l	
Sewage treatment plant	0,045 µg/l	
Soil	0,009 µg/l	

8.2. Exposure controls

Appropriate engineering controls:

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

General protective measures:

Wear suitable protective equipment.

Respiratory protection:

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection:

Nitrile rubber

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Eye protection:

Safety glasses

Body protection:

Wear suitable protective equipment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state: liquid
Form: liquid
Colour: grey

Odour: not significant Odour threshold: not required pH value: not measured Melting point: not applicable Boiling point: approx. 100 °C Flash point: > 100 °C Evaporation rate: not determined Flammability: not determined Lower explosion limit: not determined Upper explosive limit: not determined

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830 Revision Date: 04/02/2019

page 7/21

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

Combustion number: not applicable
Minimum ignition energy: not determined
Vapour pressure: not determined
Vapour density relative to air: not determined
Relative Density: no data available

Solubility in water: miscible

Octanol/ water partition

coefficient (log Pow): not determined lgnition temperature: not determined Thermal decomposition: > 100 °C Viscosity (dynamic): not tested

Oxidizing properties: no data available

9.2. Other information

Density: 2,00 g/cm³ (20 °C)

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical Stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use. Stable.

10.4. Conditions to avoid

None known.

10.5. Incompatible Materials

No data available.

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: TOXICOLOGIC INFORMATION

11.1. Information on toxicological effects Acute toxicity

Informations related to the product:

Acute oral toxicity: Remarks: no data available Acute inhalation toxicity: Remarks: no data available

Acute dermal toxicity: Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

<u>Informations related to the component 1,2-Benzisothiazol-3(2H)-one:</u>

Acute oral toxicity: LD50 (Rat, male and female): 670 - 784 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity: LC50 (Rat, male and female): 0,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: OPPTS 870.1300

GLP: yes

Acute dermal toxicity: LD50 (Rat, male and female): > 2.000 mg/kg

GLP: ves

Assessment: The substance or mixture has no acute

dermal toxicity.

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one (3:1):

Acute oral toxicity: LD50 (Rat): 64 mg/kg

Acute inhalation toxicity: LC50 (Rat, male and female): 0,171 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist LD50 (Rabbit): 92,4 mg/kg

Acute dermal toxicity: Skin corrosion/irritation

Informations related to the product:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Remarks: The toxicological data has been taken

page 8/21

from products of similar composition.

Informations related to the component Alcohols, C16-18 and C18-unsaturated, ethoxylated:

Result: Irritating to skin.

Informations related to the component 1,2-Benzisothiazol-3(2H)-one:

Species: Rabbit

Exposure time: 4 h Result:Irritating to skin.

GLP:yes

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one(3:1):

Species: Rabbit

Result: Causes burns.

Serious eye damage/eye irritation

Informations related to the product:

Species: rabbit eye

Method: OECD Test Guideline 405

Result: No eye irritation

Remarks: The toxicological data has been taken

from products of similar composition.

Informations related to the component 1,2-Benzisothiazol-3(2H)-one:

Species: rabbit eye

Exposure time: 2,9 h - 11 d

Result: Risk of serious damage to eyes.

GLP: yes

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one(3:1):

Species: rabbit eye

Result: Risk of serious damage to eyes.

Respiratory or skin sensitisation

Informations related to the product:

Remarks: no data available

Informations related to the component 1,2-Benzisothiazol-3(2H)-one:

Test Type: Guinea pig maximization test

Exposure routes: Dermal

Species: Guinea pig

Method: Other

ResulT: May cause sensitisation by skin contact.

GLP: yes

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

page 9/21

<u>Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one(3:1):</u>

Species: Guinea pig

Method: Other

Result: The product is a skin sensitiser,

sub-category 1A.

Assessment: Toxic if swallowed, Fatal in contact with skin,

Fatal ifinhaled,

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Germ cell mutagenicity

Informations related to the product:

Genotoxicity in vitro: Remarks: no data available

Germ cell mutagenicity-

Assessment: No information available.

Informations related to the component 1,2-Benzisothiazol-3(2H)-one:

Genotoxicity in vitro: Test Type: Mouse lymphoma assay

Test system: mouse lymphoma cells Concentration: 0,1 - 12,8 µg/ml

Metabolic activation:

with and without metabolic

activation: Method: OECD Test Guideline 476

Result: negative

GLP: yes

Test Type: Ames test

Test system: Salmonella typhimurium Concentration: 0,064 - 200 µg/plate

Metabolic activation:

with and without metabolic

activation: Method: OECD Test Guideline 471

Result: negative

GLP: yes

Test Type: Chromosome aberration test in vitro

Test system: Human lymphocytes Concentration: 1 - 40 µg/ml

Metabolic activation:

with and without metabolic

activation: Method: OECD Test Guideline 473

Result: positive GLP: yes Test Type: Other

Genotoxicity in vivo:

Species: Rat (male) Strain: wistar Cell type: Liver cells

Application Route: Ingestion Exposure time: single dose

Dose: 560 - 1400 mg/kg Method: OECD Test Guideline 486

Result: negative

GLP: yes

Test Type: Micronucleus test Species: Mouse (male and female)

Strain: CD1

Cell type: Bone marrow Application Route: Ingestion

CULR[™] Art Pigment for Epoxy – Ash Grey Tradename:

Exposure time: single dose

Dose: 125-250-500-1000-2000-5000mg/kg

page 10/21

Method: OECD Test Guideline 474

Result: negative GLP: yes

Germ cell mutagenicity-

Assessment: Did not show mutagenic effects in animal experiments.

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one(3:1):

Genotoxicity in vitro: Test Type: In vitro study

Metabolic activation:

with and without metabolic

activation: Result: Conflicting results have been seen in different

studies.

Genotoxicity in vivo: Test Type: Micronucleus test

Species: Rat

Cell type: Bone marrow Application Route: Oral Exposure time: ≤ 5 d Dose: $1-5 \times 28 \text{ mg/kg}$

Result: negative

Test Type: Micronucleus test

Species: Mouse Application Route: Oral Exposure time: ≤ 5 d Dose: $1-5 \times 20 - 30 \text{ mg/kg}$

Result: negative

Germ cell mutagenicity-

Assessment: In vivo tests did not show mutagenic effects

Carcinogenicity

Informations related to the product:

Carcinogenicity -

Assessment: No information available. <u>Informations related to the component 1,2-Benzisothiazol-3(2H)-one:</u>

Carcinogenicity -

Assessment: Not applicable

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one(3:1):

Carcinogenicity -

Assessment: No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Informations related to the product:

Reproductive toxicity -

No information available. Assessment: Informations related to the component 1,2-Benzisothiazol-3(2H)-one:

Effects on fertility: Species: Rat, male

> Application Route: oral (fed) Dose: 18,5 - 97,8 mg/kg

General Toxicity - Parent: NOAEL: 18,5 mg/kg

body weight

General Toxicity F1: NOAEL: 48 mg/kg body weight

Method: Other GLP: yes

CULR[™] Art Pigment for Epoxy – Ash Grey Tradename:

Species: Rat, female Application Route: oral (feed)

Dose: 27,0 - 114,8 mg/kg

General Toxicity - Parent: NOAEL: 27 mg/kg

body weight

General Toxicity F1: NOAEL: 56,6 mg/kg body weight

page 11/21

Method: Other GLP: yes

Species: Rat, female Effects on foetal development:

> Application Route: oral (gavage) Dose: 10 - 40 - 100 mg/kg

General Toxicity Maternal: NOAEL: 10 mg/kg

body weight

Teratogenicity: NOAEL: 40 mg/kg body weight Method: Directive 67/548/EEC, Annex V, B.31.

GLP: yes

Reproductive toxicity – Assessment: No evidence of adverse effects on sexual function

and fertility, or on development, based on animal

experiments.

Embryotoxicity classification not possible from current

data.

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one(3:1):

Effects on fertility: Species: Rat. male and female

Application Route: Drinking water

Dose: 25 - 75 - 225 ppm

General Toxicity - Parent: NOAEL: 16,3 - 24,7 mg/kg

body weight

General Toxicity F1: NOAEL: 16,3 - 24,7 mg/kg

body weight Method: Other GLP: yes

Species: Rat. male and female Application Route: Drinking water

Dose: 30 - 100 - 300 ppm

General Toxicity - Parent: NOAEL: 2,8 - 4,4 mg/kg

body weight

General Toxicity F1: NOAEL: 22,7 - 28 mg/kg

body weight

General Toxicity F2: NOAEL: 35,7 - 39,1 mg/kg

body weight

Method: OECD Test Guideline 416

GLP: yes

Species: Rat, male and female Effects on foetal development:

Application Route: oral (gavage)

Dose: ≤ 15 mg/kg

Developmental Toxicity: NOAEL: 15 mg/kg body weight

Method: Other

Species: Rat, male and female Application Route: oral (gavage)

General Toxicity Maternal: NOAEL: ≤ 3,95 mg/kg

body weight Method: Other

Reproductive toxicity – Assessment: Weight of evidence does not support classification for

reproductive toxicity

Embryotoxicity classification not possible from current

data.

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

STOT - single exposure

Informations related to the component product:

Remarks: no data available

Informations related to the component 1,2-Benzisothiazol-3(2H)-one:

Assessment: The substance or mixture is not classified as specific

target organ toxicant, single exposure.

page 12/21

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one(3:1):

Assessment: The substance or mixture is not classified as specific

target organ toxicant, single exposure.

STOT - repeated exposure

Informations related to the component product:

Remarks: no data available

<u>Informations related to the component 1,2-Benzisothiazol-3(2H)-one:</u>

Assessment: The substance or mixture is not classified as specific

target organ toxicant, repeated exposure.

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one(3:1):

Assessment: The substance or mixture is not classified as specific

target organ toxicant, repeated exposure.

Repeated dose toxicity

Informations related to the product:

Remarks: This information is not available.

Informations related to the component 1,2-Benzisothiazol-3(2H)-one:

Species: Dog, male and female

NOAEL: 5 mg/kg LOAEL: 20 mg/kg

Application Route: oral (gavage)

Exposure time: 90 d Number of exposures: daily Dose: 5 - 20 - 50 mg/kg

Group: yes

Method: 88/302/EC

GLP: yes

<u>Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and</u>

2-methyl-2H-isothiazol-3-one(3:1):

Species: Rat, male and female

NOAEL: 16,3 - 24,7 mg/kg ApplicationRoute: Drinking water

Exposure time: 90 d Number of exposures: daily Dose: 25 - 75 - 225 ppm

Group: yes Method: Other GLP: yes

Aspiration toxicity

Informations related to the product:

no data available

Informations related to the component 1,2-Benzisothiazol-3(2H)-one:

No aspiration toxicity classification

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

page 13/21

<u>Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one(3:1):</u>

No aspiration toxicity classification

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity:

Informations related to the product:

Toxicity to fish: Remarks: no data available

Toxicity to daphnia and other

aquatic invertebrates: Remarks: no data available Toxicity to algae: Remarks: no data available Toxicity to fish (Chronic toxicity): Remarks: no data available Toxicity to microorganisms: Remarks: no data available

Informations related to the component Alcohols, C16-18 and C18-unsaturated, ethoxylated:

M-Factor

(Acute aquatic toxicity):

Ecotoxicology Assessment

Acute aquatic toxicity: Very toxic to aquatic life.

Chronic aguatic toxicity: Harmful to aquatic life with long lasting effects.

<u>Informations related to the component 1,2-Benzisothiazol-3(2H)-one:</u>

Toxicity to fish: LC50 (Oncorhynchus mykiss (rainbow trout)): 2,18 mg/l

Exposure time: 96 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 203

GLP: yes

LC50 (Cyprinodon variegatus (sheepshead minnow)):

approx.16,7 mg/l Exposure time: 96 h Test Type: static test Analytical monitoring: yes

Method: No information available.

GLP: yes

Toxicity to daphnia and other

aquatic invertebrates: EC50 (Daphnia magna (Water flea)): 2,94 mg/l

Exposure time: 48 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 202

GLP: yes

EC0 (Daphnia magna (Water flea)): 0,643 mg/l

Exposure time: 48 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 202

GLP: yes

EC50 (Mysidopsis bahia (opossum shrimp)): 0,9893 mg/l

Exposure time: 96 h
Test Type: static test
Analytical monitoring: yes

Method: Other GLP: yes

Remarks: salt water

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

NOEC (Mysidopsis bahia (opossum shrimp)): 0,25 mg/l

page 14/21

Exposure time: 96 h
Test Type: static test
Analytical monitoring: yes

Method: Other GLP: yes

Remarks: salt water

Toxicity to algae: EC50 (Selenastrum capricornutum (green algae)):

0,155 mg/l

End point: Growth rate Exposure time: 72 h Analytical monitoring: yes

Method: OECD Test Guideline 201

GLP: yes

NOEC (Selenastrum capricornutum (green algae)):

0,055 mg/l

End point: Growth rate Exposure time: 72 h Analytical monitoring: yes

Method: OECD Test Guideline 201

GLP: yes

1

M-Factor

(Acute aquatic toxicity):

sewage): 23 mg/l

End point: Bacteria toxicity (respiration inhibition)

Exposure time: 3 h
Test Type: aquatic
Analytical monitoring: no

Method: OECD Test Guideline 209

GLP: yes

Remarks: The details of the toxic effect relate to the

nominal concentration.

EC50: > 811,5 mg/kg dry weight (d.w.)

Exposure time: 28 d Test Type: Soil

Analytical monitoring: yes Method: OECD 216

GLP: yes

Remarks: The details of the toxic effect relate to the

nominal concentration.

NOEC: 263,7 mg/kg dry weight (d.w.)

Exposure time: 28 d Test Type: Soil

Analytical monitoring: yes Method: OECD 216

GLP: yes

Remarks: The details of the toxic effect relate to the

nominal concentration.

Toxicity to fish

(Chronic toxicity): NOEC: 0,21 mg/l

Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Analytical monitoring: yes

Method: OECD Test Guideline 215

GLP: yes

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity):

NOEC: 1,2 mg/l

End point: Reproduction rate

Exposure time: 21 d

Species: Daphnia magna (Water flea)

page 15/21

Analytical monitoring: yes

Method: OECD Test Guideline 211

GLP: yes

NOEC: 1,9 mg/l

End point: Reproduction rate

Exposure time: 21 d

Species: Daphnia magna (Water flea)

Analytical monitoring: yes

Method: OECD Test Guideline 211

GLP: yes

Toxicity to soil dwelling organisms:

Test Type: artificial soil LC50: > 410,6 mg/kg Exposure time: 14 d End point: mortality

Species: Eisenia fetida (earthworms) Method: OECD Test Guideline 207

GLP:yes

Remarks: The details of the toxic effect relate to the

nominal concentration.

Test Type: artificial soil NOEC: 234,5 mg/kg Exposure time: 14 d End point: mortality

Species: Eisenia fetida (earthworms) Method: OECD Test Guideline 207

GLP:yes

Remarks: The details of the toxic effect relate to the

nominal concentration.

Plant toxicity: EC50: 340 mg/kg
Exposure time: 20 d
End point: Growth

Species: Phaseolus vulgaris Analytical monitoring: yes Method: OECD Guide-line 208

GLP:yes

Remarks: The details of the toxic effect relate to the

nominal concentration.

NOEC: 90 mg/kg Exposure time: 20 d End point: Growth

Species: Phaseolus vulgaris Analytical monitoring: yes Method: OECD Guide-line 208

GLP:yes

Remarks: The details of the toxic effect relate to the

nominal concentration.

EC50: 300 mg/kg Exposure time: 19 d End point: Growth

CULR[™] Art Pigment for Epoxy – Ash Grey Tradename:

Species: Triticum aestivm (wheat) Analytical monitoring: yes Method: OECD Guide-line 208

GLP: yes

Remarks: The details of the toxic effect relate to the

page 16/21

nominal concentration.

NOEC: 51 mg/kg Exposure time: 19 d End point: Growth

Species: Triticum aestivm (wheat) Analytical monitoring: yes Method: OECD Guide-line 208

GLP:yes

Remarks: The details of the toxic effect relate to the

nominal concentration.

Sediment toxicity: Remarks: not available

Ecotoxicology Assessment

Acute aquatic toxicity: Very toxic to aquatic life.

Chronic aquatic toxicity: Toxic to aquatic life with long lasting effects.

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one(3:1):

EC50 (Oncorhynchus mykiss (rainbow trout)): 0,22 mg/l Toxicity to fish:

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates: EC50 (Daphnia magna (Water flea)): 0,1 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae: EC50 (Skeletonema costatum (marine diatom)):

> 0,0052 mg/l Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 201

NOEC (Skeletonema costatum (marine diatom)):

0,00049 mg/l Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 201

M-Factor

(Acute aquatic toxicity): 100

Toxicity to microorganisms: EC50 (activated sludge): 7,92 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to fish

(Chronic toxicity): NOEC: 0,098 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 215

Toxicity to daphnia and other

aquatic invertebrates

NOEC: 0.004 mg/l (Chronic toxicity): Exposure time: 21 d

> Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202

M-Factor

(Chronic aquatic toxicity): 10

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

Toxicity to soil dwelling

organisms: LC50: 86,6 mg/kg dry weight (d.w.)

Exposure time: 14 d

Species: Eisenia fetida (earthworms) Method: OECD Test Guideline 207 NOEC: 8,83 mg/kg dry weight (d.w.) page 17/21

Exposure time: 14 d

Species: Eisenia fetida (earthworms)

OECD Test Guideline 207

Ecotoxicology Assessment

Acute aquatic toxicity: Very toxic to aquatic life.

Chronic aquatic toxicity: Very toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Informations related to the product:

Biodegradability: no data available

<u>Informations related to the component 1,2-Benzisothiazol-3(2H)-one:</u>

Biodegradability: Test Type: aerobic

Inoculum: activated sludge Concentration: 1 mg/l

Result: Partially biodegradable.

Exposure time: 63 d

Method: OECD Test Guideline 301C

GLP: yes

Physico-chemical removability: Remarks: Biodegradable

Stability in water:

Test Type: abiotic

Degradation half life: 219 d

pH: 4

Hydrolysis: at 50 °C

Method: OECD Test Guideline 111

GLP: yes

Test Type: abiotic

Degradation half life: > 200 d

pH: 7

Hydrolysis: at 50 °C

Method: OECD Test Guideline 111

GLP: yes

Test Type: abiotic

Degradation half life: 145 d

pH: 9

Hvdrolvsis: at 50 °C

Method: OECD Test Guideline 111

GLP: yes

Photodegradation: Test Type: water

Light source: Xenon lamp Light spectrum: 290 - 400 nm

Degradation (direct photolysis): < 1,5 %

GLP: yes

Test Type: air Method: calculated

GLP: no

Remarks: Decomposes rapidly in contact with light.

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830 Revision Date: 04/02/2019

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one(3:1):

Biodegradability: Test Type: aerobic

Inoculum: activated sludge Result: Not rapidly biodegradable Method: OECD Test Guideline 301B page 18/21

Photodegradation: Test Type: water

Light source: Sunlight

12.3. Bioaccumulative potential

Informations related to the product:

Bioaccumulation: no data available

Informations related to the component 1,2-Benzisothiazol-3(2H)-one:

Bioaccumulation: Species: Lepomis macrochirus (Bluegill sunfish)

Exposure time: 56 d Concentration: 0,1 mg/l

Bioconcentration factor (BCF): 6,62 Method: OECD Test Guideline 305

GLP: no

Remarks: Due to the distribution coefficient n-octanol/water,accumulation in organisms is

not expected.

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one(3:1):

Bioaccumulation: Bioconcentration factor (BCF): 3,6

Method: calculated

Remarks: Does not accumulate in organisms.

Partition coefficient

n-octanol/water: log Pow: -0,71 - 0,75

Method: OECD Test Guideline 107

12.4. Mobility in soil

<u>Informations related to the component 1,2-Benzisothiazol-3(2H)-one:</u>

Distribution among

environmental compartments: Adsorption/Soil

Medium: water – soil Koc: 235 – 566 Method: Other

12.5. Results of PBT and vPvB assessment

Informations related to the product:

This substance/mixture contains no components considered to be either persistent,

bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0,1 % or higher.

Informations related to the component 1,2-Benzisothiazol-3(2H)-one:

Assessment: The substance is not identified as a PBT or as a vPvB

substance.

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one(3:1):

Assessment: This substance is not considered to be persistent,

bioaccumulating and toxic (PBT).

12.6. Other adverse effects

Informations related to the product:

Environmental fate and pathways: no data available Additional ecological information: no data available

Safety Data Sheet

in acc. with Regulation (EU) No. 2015/830 Revision Date: 04/02/2019

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

Informations related to the component 1,2-Benzisothiazol-3(2H)-one:

Environmental fate and pathways: not available

Additional ecological information: Do not allow to enter ground water, waterways or

waste water.

Informations related to the component mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and

2-methyl-2H-isothiazol-3-one(3:1):

Additional ecological information: The product should not be allowed to enter drains,

watercourses or the soil.

page 19/21

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product:

Dispose of in accordance with the European Directives on waste and hazardous waste.

Uncleaned packaging:

This material and its container must be disposed of in a safe way.

SECTION 14: TRANSPORT INFORMATION

14.1. to 14.5.

ADR: not restricted
ADN: not restricted
RID: not restricted
IATA: not restricted
IMDG: not restricted

14.6. Special precautions for users

See sections 6 to 8 of this Safety Data Sheet.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No transport as bulk according IBC-Code.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of

Very High Concern for Authorisation (Article 59): Not applicable

REACH - List of substances subject to authorisation

(Annex XIV): Not applicable

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer: Not applicable

Regulation (EC) No 850/2004 on persistent

organic pollutants: Not applicable

Other regulations:

Apart from the data/regulations specified in this chapter, no further information is available concerning safety, health and environmental protection.

15.2. Chemical safety assessment

No Chemical Safety Assessment (CSA) is yet available for the substance, or for the component substances, contained in this product.

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey page 20/21

SECTION 16: OTHER INFORMATION

Observe the legal requirements nationally and locally.

List of the text of the hazard statements mentioned section 3 (H-phrases):

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.
 Toxic to aquatic life with long lasting effects.
 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.: Acute toxicity

Aquatic Acute: Short-term (acute) aquatic hazard Aquatic Chronic: Long-term (chronic) aquatic hazard

Eye Dam.: Serious eye damage Skin Corr.: Skin corrosion Skin Irrit.: Skin sensitisation Skin sensitisation

STOT RE: Specific target organ toxicity - repeated exposure

Change compared to the previous version:

Change in the composition

Legend

ADN European Agreement concerning the International Carriage of

Dangerous Goods by Inland Waterways

ADR European Agreement concerning the International Carriage of

Dangerous Goods by Road

AICS Australian Inventory of Chemical Substances
ASTM American Society for the Testing of Materials

bw Body weight

CLP Classification Labelling Packaging Regulation

Regulation (EC) No 1272/2008

CMR Carcinogen, Mutagen or Reproductive Toxicant
DIN Standard of the German Institute for Standardisation
DMEL Derived Minimal Effect Level (genotoxic substances)

DNEL Derived No Effect Level

DSL Domestic Substances List (Canada)
ECHA European Chemicals Agency
EC-Number European Community number

ECx Concentration associated with x% response ELx Loading rate associated with x% response

EmS Emergency Schedule

ENCS Existing and New Chemical Substances (Japan)

ErCx Concentration associated with x% growth rate response

GHS Globally Harmonized System
GLP Good Laboratory Practice

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC International Code for the Construction and Equipment of Ships

carrying Dangerous Chemicals in Bulk

IC50 Half maximal inhibitory concentration ICAO International Civil Aviation Organization

page 21/21

Tradename: CULR[™] Art Pigment for Epoxy – Ash Grey

IECSC IMDG IMO ISHL	Inventory of Existing Chemical Substances in China International Maritime Dangerous Goods International Maritime Organization Industrial Safety and Health Law (Japan)
ISO KECI	International Organisation for Standardization
LC50	Korea Existing Chemicals Inventory Lethal Concentration to 50 % of a test population
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
MARPOL	International Convention for the Prevention of Pollution from Ships
n.o.s.	Not Otherwise Specified
NO(A)EC	No Observed (Adverse) Effect Concentration
NO(A)EL	No Observed (Adverse) Effect Level
NOELR	No Observable Effect Loading Rate
NZIoC	New Zealand Inventory of Chemicals
OECD	Organization for Economic Co-operation and Development
OPPTS	Office of Chemical Safety and Pollution Prevention
PBT	Persistent, Bioaccumulative and Toxic substance
PICCS	Philippines Inventory of Chemicals and Chemical Substances
(Q)SAR	(Quantitative) Structure Activity Relationship
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SADT	Self-Accelerating Decomposition Temperature
SDS	Safety Data Sheet
TCSI	Taiwan Chemical Substance Inventory
TRGS	Technical Rule for Hazardous Substances
TSCA	Toxic Substances Control Act (United States)
UN	United Nations
vPvB	Very Persistent and Very Bioaccumulative

Decimal notation: "thousands" places are identified with a dot (for example, "2.000 mg/kg" means "two thousand mg/kg"). Decimal places are identified with a comma (for example, "1,35 g/cm³" means "one point three five g/cm³").

This information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. Easy Composites Ltd makes no warranties, express or implied, as to the information accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of CULR products for its particular application. Nothing included in this information waives any of Easy Composite's General Terms and Conditions of Sale, which control unless it agrees otherwise in writing.

Any existing intellectual/industrial property rights must be observed. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change. Material Safety Data Sheets providing safety precautions, that should be observed when handling or storing CULR products, are available upon request and are provided in compliance with applicable law. You should obtain and review the applicable Material Safety Data Sheet information before handling any of these products.

For additional information, please contact Easy Composites Ltd.