

Revision nr.1 Dated 24/03/2023 First compilation Printed on 24/03/2023 Page n. 1 / 12

Permabond ET5429A

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking				
1.1. Product identifier				
Product name	Permabond ET5429A			
1.2. Relevant identified uses of the substance or m	ixture and uses advised against			
Intended use	Adhesive			
1.3. Details of the supplier of the safety data sheet				
Name Full address District and Country e-mail address of the competent person	Permabond Engineering Adhesives Niederkasseler Lohweg 18 40547 Düsseldorf Germany Tel. +44 (0)1962 711 661			
responsible for the Safety Data Sheet	info.europe@permabond.com			
Supplier:	Permabond Engineering Adhesives Ltd Wessex Way, Colden Common, Winchester, Hampshire SO21 1WP, UK tel: +44 (0)1962 711 661 mail: info.europe@permabond.com			
1.4. Emergency telephone number				
For urgent inquiries refer to	+44 (0)1962 711 661 (8.00 am-5.00 pm Mon-Fri)			
	CHEMTREC UK: +(44)-870-8200418 CHEMTREC Ireland: +(353)-19014670 CHEMTREC Australia: +(61)-290372994 CHEMTREC New Zealand: +(64)-98010034			

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic	H411	Toxic to aquatic life with long lasting effects.
toxicity, category 2		

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Permabond ET5429A

SECTION 2. Hazards identification/>>

Signal words:	Warning
Hazard statements:	
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
Precautionary statements:	
P273	Avoid release to the environment.
P280	Wear protective gloves / protective clothing / eve protection / face protection.
P302+P352	In case of contact with the skin: wash abundantly with soap and water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Contains:	EPOXY RESIN (Number average MW <= 700) 1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\ge 0.1\%$.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
EPOXY RESI	N (Number average MW <= 700)	
INDEX	$30 \le x < 60$	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411, EUH205
EC	216-823-5	Skin Irrit. 2 H315: ≥ 5%, Eye Irrit. 2 H319: ≥ 5%
CAS	1675-54-3	
REACH Reg.	01-2119456619-26-XXXX	
1,4-BIS[(2,3-E	POXYPROPOXY)METHYL]CYCLOHEXA	NE
INDEX	10 ≤ x < 25	Acute Tox. 4 H302, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 3 H412
EC	238-098-4	LD50 Oral: 1098 mg/kg
CAS	14228-73-0	
REACH Reg.	01-2120068066-56-XXXX	
[3-(2,3-EPOX)	YPROPOXY) PROPYL] TRIMETHOXYSIL	ANE
INDEX	, 1≤x< 3	Eye Dam. 1 H318, Aquatic Chronic 3 H412
EC	219-784-2	
CAS	2530-83-8	
REACH Reg.	01-2119513212-58-XXXX	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

Skin: Wash the skin thoroughly with soap and water. If symptoms arise, request medical assistance

Eyes: Make sure you have removed any contact lenses before rinsing your eyes. Wash

Readyly and abundantly the eyes with water keeping the eyelids open.

Continue to rinse for at least 15 minutes. Consult a doctor if the discomfort continues.

Ingestion: rinse the mouth with water thoroughly. Make a abundant quantity of water drink.

Do not cause vomiting. Consult a doctor.

Inhalation: move the subject exposed in the open air. Consult a doctor in case of serious symptoms or persistent.

@EPY 11.4.1 - SDS 1004.14



SECTION 4. First aid measures ... / >>

4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash. Contact with eyes: irritating and can cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor no specific recommendation. Symptomatic treatment.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away

SECTION 7. Handling and storage ... / >>

from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Permabond

Adhesive

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

			(Y RESIN (Num	nber average N	WW <= 700)			
redicted no-effect cor	ncentration	- PNEC						
Normal value in fresh	0,006	mg/l						
Normal value in mari	ne water					0,001	mg/l	
Normal value for fres	h water sed	liment				0,341	mg/kg	
Normal value for mar	ine water se	ediment				0,034	mg/kg	
Normal value of STP	microorgan	lisms				10	mg/l	
Normal value for the	food chain (secondary poisor	ning)			11	mg/kg	
Normal value for the	terrestrial co	ompartment				0,065	mg/kg	
ealth - Derived no-eff	ect level - C	ONEL / DMEL						
	Effects o	n consumers			Effects on v	vorkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				0,5				
				mg/kg/d				
Inhalation				0,87				4,93
				mg/m3				mg/m3
Skin				0,0893				0,75
				mg/kg/d				mg/kg/d
			B-EPOXYPROP	OXY)METHYL]CYCLOHEXA	NE		
redicted no-effect cor		I - PNEC						
Normal value in fresh						0,117	mg/l	
Normal value in marine water						0,012	mg/l	
Normal value for fresh water sediment						0,47	mg/kg	
Normal value for marine water sediment						0,047	mg/kg	
Normal value of STP microorganisms						0,6	mg/l	
Normal value for the	· · · · ·	·	ning)			1	mg/kg	
Normal value for the						0,24	mg/kg	
lealth - Derived no-eff	ect level - D	ONEL / DMEL						
Effects on consumers Ef						vorkers		

		loonoannoio						
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				0,5				
				mg/kg bw/d				
Inhalation				0,86				3,52
				mg/m3				mg/m3
Skin				0,5				1
				mg/kg bw/d				mg/kg
								bw/d



SECTION 8. Exposure controls/personal protection

[3-(2,3-EPOXYPROPOXY) PROPYL] TRIMETHOXYSILANE

		Le (=,e =: e						
Predicted no-effect cor	ncentration	- PNEC						
Normal value in fresh	water					0,45	mg/l	
Normal value in marin	ne water					0,045	mg/l	
Normal value for fres	h water sedi	ment				1,6	mg/kg/d	
Normal value for mar	ine water se	diment				0,16	mg/kg/d	
Normal value for wate	er, intermitte	nt release				0,45	mg/l	
Normal value of STP	microorgani	sms				8,2	mg/l	
Normal value for the	terrestrial co	mpartment				0,063	mg/kg/d	
lealth - Derived no-eff	ect level - D	NEL / DMEL					0 0	
	Effects or	n consumers			Effects on v	vorkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				5				
				mg/kg bw/d				
Inhalation		26400		17		26400		70.5
		mg/m3		mg/m3				mg/m3
Skin				5				10
				mg/kg bw/d				mg/kg
								IIIU/KU

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Value
paste
white or brow
characteristic
not available
not available
not available

vhite or brown characteristic ot available not available

Information



Permabond ET5429A

SECTION 9. Physical and chemical properties/>>

Lower explosive limit Upper explosive limit Flash point Auto-ignition temperature Decomposition temperature pH Kinematic viscosity Dynamic viscosity Solubility Partition coefficient: n-octanol/water Vapour pressure Density and/or relative density Relative vapour density

not available not available 100 °C not available not available not available c 65000 mPa s

>

~ 65000 mPa.s Thixo not available not available not available 1,1 not available not applicable Reason for missing data:substance/mixture is non-soluble (in water)

Revision nr.1 Dated 24/03/2023

First compilation

Printed on 24/03/2023 Page n. 6 / 12

Temperature: 25 °C

9.2. Other information

Particle characteristics

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available



Permabond ET5429A

Revision nr.1 Dated 24/03/2023 First compilation Printed on 24/03/2023 Page n. 7 / 12

SECTION 11. Toxicological information ... / >>

Delayed and immediate effects as well as chronic effects from short and long-term exposure Information not available Interactive effects Information not available ACUTE TOXICITY ATE (Inhalation) of the mixture: Not classified (no significant component) ATE (Oral) of the mixture: >2000 mg/kg ATE (Dermal) of the mixture: Not classified (no significant component) EPOXY RESIN (Number average MW <= 700) LD50 (Dermal): > 2000 mg/kg > 2000 mg/kg LD50 (Oral): 1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE LD50 (Dermal): > 2000 mg/kg LD50 (Oral): 1098 mg/kg [3-(2,3-EPOXYPROPOXY) PROPYL] TRIMETHOXYSILANE LD50 (Dermal): 4250 mg/kg Rabbit - New Zeland white LD50 (Oral): 8025 mg/kg Rat - Wistar LC50 (Inhalation vapours): 5,3 mg/l Rat - Fischer 344 SKIN CORROSION / IRRITATION Causes skin irritation SERIOUS EYE DAMAGE / IRRITATION Causes serious eye irritation RESPIRATORY OR SKIN SENSITISATION Sensitising for the skin GERM CELL MUTAGENICITY Does not meet the classification criteria for this hazard class CARCINOGENICITY Does not meet the classification criteria for this hazard class REPRODUCTIVE TOXICITY Does not meet the classification criteria for this hazard class STOT - SINGLE EXPOSURE Does not meet the classification criteria for this hazard class STOT - REPEATED EXPOSURE Does not meet the classification criteria for this hazard class ASPIRATION HAZARD Does not meet the classification criteria for this hazard class 11.2. Information on other hazards Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.



Permabond ET5429A

SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity

EPOXY RESIN (Number average MW <= 700)	
LC50 - for Fish	2 mg/l/96h
EC50 - for Crustacea	1,8 mg/l/48h
EC50 - for Algae / Aquatic Plants	11 mg/l/72h
Chronic NOEC for Crustacea	0,3 mg/l
Chronic NOEC for Algae / Aquatic Plants	4,2 mg/l
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHE	EXANE
LC50 - for Fish	10,1 mg/l/96h

LC50 - for Fish	10,1 mg/i/96n
EC50 - for Crustacea	16,3 mg/l/48h
EC50 - for Algae / Aquatic Plants	36,6 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	25 mg/l

 [3-(2,3-EPOXYPROPOXY) PROPYL] TRIMETHOXYSILANE

 LC50 - for Fish
 55 mg/l/96h Cyprinus carpio

 EC50 - for Crustacea
 324 mg/l/48h Simocephalus vetulus

12.2. Persistence and degradability

EPOXY RESIN (Number average MW <= 700) NOT rapidly degradable

1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE NOT rapidly degradable

[3-(2,3-EPOXYPROPOXY) PROPYL] TRIMETHOXYSILANE NOT rapidly degradable

12.3. Bioaccumulative potential

EPOXY RESIN (Number average MW <= 700) BCF 31

[3-(2,3-EPOXYPROPOXY) PROPYL] TRIMETHOXYSILANE Partition coefficient: n-octanol/water -2,6

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available



Permabond ET5429A

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Waste class 08 04 09* stickers and sealed sealing, containing organic solvents or other dangerous substances.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to ADR provisions.

- IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to IMDG Code provisions.
- IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity \leq 5Kg or 5L, is not submitted to IATA dangerous goods regulations.

14.2. UN proper shipping name

 ADR / RID:
 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW ≤ 700))

 IMDG:
 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW ≤ 700))

 IATA:
 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW ≤ 700))

14.3. Transport hazard class(es)

ADR / RID:	Class: 9	Label: 9	
IMDG:	Class: 9	Label: 9	
IATA:	Class: 9	Label: 9	

14.4. Packing group

ADR / RID, IMDG, IATA: III



Permabond ET5429A

Revision nr.1 Dated 24/03/2023 First compilation Printed on 24/03/2023 Page n. 10 / 12

SECTION 14. Transport information ... / >>

14.5. Environmental hazards

		•
ADR / RID:	Environmentally Hazardous	
IMDG:	Marine Pollutant	
IATA:	Environmentally Hazardous	
	adr / Rid: IMdg:	IMDG: Marine Pollutant

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 90 Special provision: -	Limited Quantities: 5 L	Tunnel restriction code: (-)
IMDG:	EMS: F-A, S-F	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 450 L	Packaging instructions: 964
	Pass.:	Maximum quantity: 450 L	Packaging instructions: 964
	Special provision:	A97, A158, A197, A215	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

E2

Product Point

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

3

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention: None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017) WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

ΕN



Revision nr.1 Dated 24/03/2023 First compilation Printed on 24/03/2023 Page n. 11 / 12

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4 Eye Dam. 1 Eye Irrit. 2 Skin Irrit. 2 Skin Sens. 1 Aquatic Chronic 2 Aquatic Chronic 3 H302 H318 H319 H315 H317 H411 H412 ELH205	Acute toxicity, category 4 Serious eye damage, category 1 Eye irritation, category 2 Skin irritation, category 2 Skin sensitization, category 1 Hazardous to the aquatic environment, chronic toxicity, category 2 Hazardous to the aquatic environment, chronic toxicity, category 3 Harmful if swallowed. Causes serious eye damage. Causes serious eye damage. Causes serious eye irritation. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)



Revision nr.1 Dated 24/03/2023 First compilation Printed on 24/03/2023 Page n. 12 / 12

Permabond ET5429A

SECTION 16. Other information ... / >>

- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148

Permabond[®]

- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

FN

Deman	hond
Perma	
Engineerin	g Adhesives

Revision nr.1 Dated 22/03/2023 First compilation Printed on 22/03/2023 Page n. 1 / 12

Permabond ET5429B

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

S	ECTION 1. Identification of the subs	tance/mixt	ure and of the com	pany/undertak	king							
1.'	I. Product identifier											
	Product name	Permabond E	T5429B									
1.:	1.2. Relevant identified uses of the substance or mixture and uses advised against											
	Intended use	Adhesive										
	Identified Uses	Industrial	Professional		Consumer							
	Use	\checkmark	 Image: A second s		-							
1.:	3. Details of the supplier of the safety data sheet											
	Name	Permabond E	ngineering Adhesives									
	Full address	Niederkassel										
	District and Country		Düsseldorf									
	Biother and Country		Germany									
			+44 (0)1962 711 661									
	e-mail address of the competent person	101.										
	responsible for the Safety Data Sheet	info.europe@	permabond.com									
	Supplier:	Permabond E	ngineering Adhesives Ltd									
			Colden Common,									
			lampshire SO21 1WP, UK									
		tel: +44 (0)19	•									
			ope@permabond.com									
			oho@hourage									
1.4	4. Emergency telephone number											
	For urgent inquiries refer to	+44 (0)1962 7	11 661 (8.00 am-5.00 pm	Mon-Fri)								
		CHEMTREC L	JK: +(44)-870-8200418									
			reland: +(353)-19014670									
			Australia: +(61)-290372994									
			lew Zealand: +(64)-980100	34								
SE	CTION 2. Hazards identification											

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Skin corrosion, category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 2	H411	Toxic to aquatic life with long lasting effects.

EN



Permabond ET5429B

Revision nr.1 Dated 22/03/2023 First compilation Printed on 22/03/2023 Page n. 2 / 12

SECTION 2. Hazards identification ... / >>

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:	Danger
Hazard statements:	
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
Precautionary statements:	
P273	Avoid release to the environment.
P280	Wear protective gloves / protective clothing / eye protection / face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352	In case of contact with the skin: wash abundantly with soap and water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice / attention.
Contains:	3,3'-OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)
Contains.	POLYAMINOAMIDE
	ATBN POLYMER
	2-piperazin-1-vlethylamine

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\ge 0.1\%$.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:			
Identification		x = Conc. %	Classification (EC) 1272/2008 (CLP)
POLYAMINO	AMIDE		
INDEX		$30 \le x \le 60$	Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411
EC	500-191-5		
CAS	68082-29-1		
REACH Reg.	01-2119972320-	44-XXXX	
ATBN POLYN			
INDEX		10 ≤ x < 30	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1B H317
EC			
CAS	68683-29-4		
2,4,6-TRIS(DI	METHYLAMINOM	ETHYL)PHENOL	
INDEX	603-069-00-0	10 ≤ x < 25	Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC	202-013-9		STA Oral: 500 mg/kg
CAS	90-72-2		
REACH Reg.	01-2119560597-	27-XXXX	
0			



Permabond ET5429B

Revision nr.1 Dated 22/03/2023 First compilation Printed on 22/03/2023 Page n. 3 / 12

SECTION 3. Composition/information on ingredients/>>

INDEX		5≤x< 10	Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317
EC	224-207-2		
CAS	4246-51-9		
REACH Reg.	01-2119963377-	26-XXXX	
2-piperazin-1-	-ylethylamine		
INDEX	612-105-00-4	$0,1 \le x \le 1$	Repr. 2 H361, Acute Tox. 3 H311, Acute Tox. 4 H302, STOT RE 2 H373, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Chronic 3 H41
EC	205-411-0		STA Oral: 500 mg/kg, LD50 Dermal: 866 mg/kg
CAS	140-31-8		
REACH Req.	01-2119471486-	30-XXXX	

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

Skin: Wash the skin thoroughly with soap and water. If symptoms arise, request medical assistance Eyes: Make sure you have removed any contact lenses before rinsing your eyes. Wash Readyly and abundantly the eyes with water keeping the eyelids open. Continue to rinse for at least 15 minutes. Consult a doctor if the discomfort continues. Ingestion: rinse the mouth with water thoroughly. Make a abundant quantity of water drink. Do not cause vomiting. Consult a doctor. Inhalation: move the subject exposed in the open air. Consult a doctor in case of serious symptoms or persistent.

4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash. Contact with eyes: irritating and can cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor no specific recommendation. Symptomatic treatment.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent



Permabond ET5429B

SECTION 6. Accidental release measures/>>

any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Adhesive

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

		246-1	RIS(DIMETHY					
Predicted no-effect con	centration				,			
Normal value in fresh	water					84	mg/l	
Normal value in marin	e water					84	mg/l	
Health - Derived no-effe	ct level - D	NEL / DMEL						
	Effects or	n consumers			Effects on v	vorkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation							0,31	
							mg/m3	

FN



2-piperazin-1-ylethylamine

SECTION 8. Exposure controls/personal protection .../>>

			2-piperazii	n-1-yietnyiamin	e			
Predicted no-effect con		- PNEC						
Normal value in fresh						0,058	mg/l	
Normal value in marin	ie water					0,006	mg/l	
Normal value for fresh	n water sedir	ment				215	mg/kg	
Normal value for mari	ne water see	diment				21,51	mg/kg	
Normal value for mari	ne water, int	termittent release	Э			0,58	mg/l	
Normal value of STP	microorganis	sms				250	mg/l	
lealth - Derived no-effe	ect level - D	NEL / DMEL					-	
	Effects or	consumers			Effects on w	orkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation		,		,	80	10.6	0.015	10.6
					mg/m3	mg/m3	mg/m3	mg/m3
Skin								3.33
								mg/kg
								bw/d
								Dw/u
				MINOAMIDE				
Predicted no-effect con	centration	- PNEC	10217					
Normal value in fresh	water					0,004	mg/l	
Normal value in marin						0	mg/l	
Normal value for fresh		ment				434,02	mg/kg/d	
Normal value for mari						43,4	mg/kg/d	
Normal value of STP						3,84	mg/l	
Normal value for the t	0					86,78	mg/kg/d	
Health - Derived no-effe						00,70	mg/kg/u	
icalui - Deriveu no-ene					Effects on w	orkoro		
		consumers	Ohmenia	Ohmenia			Ohmenia	Olympia
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				0.0972				0.952
				mg/kg bw/d				
Inhalation				0.169				0.952
				mg/m3				mg/m3
Skin				0.0972				0.272
				mg/kg bw/d				mg/kg
				00				bw/d
		3,3'-OX	YBIS(ETHYLEN	EOXY)BIS(PRO	OPYLAMINE)			
Predicted no-effect con	centration			, ,				
Normal value in fresh	water					0,22	mg/l	
Normal value in marin	e water					0.022	mg/l	
Normal value for fresh		ment				1,1	mg/kg/d	
Normal value for mari						0,11	mg/kg/d	
Normal value of STP						500	mg/l	
Normal value for the t							mg/kg/d	
Health - Derived no-effe						0,091	mg/kg/u	
realth - Derived no-effe					Effects and	arkara		
		consumers		<u>.</u>	Effects on w		<u>.</u>	<u>.</u>
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				5				
				mg/kg/d				
Inhalation	6.5	52	0.5	17	13	176	1	59
		mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3	mg/m3
	mg/m3				IIIq/IIIJ			
Skin	mg/m3	ing/ino	mg/mo		ing/ino	iiig/iiio		
Skin	mg/m3	mg/mo	ing/ino	5 mg/kg/d	ilig/ilio	ing/ine		8.3 mg/kg/d

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.



Permabond ET5429B

SECTION 8. Exposure controls/personal protection ... />

Revision nr.1 Dated 22/03/2023 First compilation Printed on 22/03/2023 Page n. 6 / 12

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information		
Appearance	paste			
Colour	black			
Odour	amino			
Melting point / freezing point	not available			
Initial boiling point	not available			
Flammability	not available			
Lower explosive limit	not available			
Upper explosive limit	not available			
Flash point >	100 °C			
Auto-ignition temperature	not available			
Decomposition temperature	not available			
pH	not available	Reason for missing d	lata:substan	ce/mixture is
•		non-soluble	(in	water)
Kinematic viscosity	not available		,	,
Dynamic viscosity	~ 150000 mPa.s Thixo	Temperature: 23 °C		
Solubility	not available	•		
Partition coefficient: n-octanol/water	not available			
Vapour pressure	not available			
Density and/or relative density	1			
Relative vapour density	not available			
Particle characteristics	not applicable			

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

@EPY 11.4.1 - SDS 1004.14



Revision nr.1 Dated 22/03/2023 First compilation Printed on 22/03/2023 Page n. 7 / 12

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: ATE (Oral) of the mixture: ATE (Dermal) of the mixture: Not classified (no significant component) >2000 mg/kg >2000 mg/kg

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL STA (Oral):

2-piperazin-1-ylethylamine LD50 (Dermal): LD50 (Oral): STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

866 mg/kg 2140 mg/kg 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture) ΕN



Permabond ET5429B

SECTION 11. Toxicological information ... / >>

POLYAMINOAMIDE	
LD50 (Dermal):	> 2000 mg/kg
LD50 (Oral):	> 2000 mg/kg
ATBN POLYMER	
LD50 (Dermal):	> 2000 mg/kg
LD50 (Oral):	> 2000 mg/kg
3,3'-OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)	

 LD50 (Dermal):
 > 2150 mg/kg

 LD50 (Oral):
 3160 mg/kg

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity

2-piperazin-1-ylethylamine LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants	2190 mg/l/96h 58 mg/l/48h > 1000 mg/l/72h
POLYAMINOAMIDE LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants	7,07 mg/l/96h 7,07 mg/l/48h 4,34 mg/l/72h

Revision nr.1 Dated 22/03/2023

First compilation

Printed on 22/03/2023 Page n. 8 / 12



Revision nr.1 Dated 22/03/2023 First compilation Printed on 22/03/2023 Page n. 9 / 12

SECTION 12. Ecological information ... / >>

12.2. Persistence and degradability

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL Solubility in water > 10000 mg/l NOT rapidly degradable

12.3. Bioaccumulative potential

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL Partition coefficient: n-octanol/water -0,66

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Waste class 08 04 09* stickers and sealed sealing, containing organic solvents or other dangerous substances.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 2735

14.2. UN proper shipping name

ADR / RID:	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.
IMDG:	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.
IATA:	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.

Permabond[®]

Permabond Engineering Adhesives

Permabond ET5429B

Revision nr.1 Dated 22/03/2023 First compilation Printed on 22/03/2023 Page n. 10 / 12

SECTION 14. Transport information ... / >>

14.3. Transport hazard class(es)

ADR / RID:	Class: 8	Label: 8	
IMDG:	Class: 8	Label: 8	
IATA:	Class: 8	Label: 8	



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID:	NO
IMDG:	NO
IATA:	NO

14.6. Special precautions for user

ADR / RID:

IMDG: IATA: HIN - Kemler: 80 Special provision: 274 EMS: F-A, S-B Cargo: Pass.: Special provision: Limited Quantities: 5 L

Limited Quantities: 5 L Maximum quantity: 60 L Maximum quantity: 5 L A3, A803 Tunnel restriction code: (E)

Packaging instructions: 856 Packaging instructions: 852

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006 Product Point 3 Contained substance 75 Point Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable Substances in Candidate List (Art. 59 REACH) On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%. Substances subject to authorisation (Annex XIV REACH) None Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012: None Substances subject to the Rotterdam Convention: None Substances subject to the Stockholm Convention: None

E2

Healthcare controls



Permabond ET5429B

Revision nr.1 Dated 22/03/2023 First compilation Printed on 22/03/2023 Page n. 11 / 12

SECTION 15. Regulatory information ... / >>

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017) WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1B	Skin sensitization, category 1B
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H361	Suspected of damaging fertility or the unborn child.
H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation

ΕN



Revision nr.1

SECTION 16. Other information ... / >>

- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition

- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.