

**SAFETY DATA SHEET**

VE140 Fuel Resistant Vinylester Resin

Date revised: 26.01.2023

Version: 3 / GB

Master No. M-401

Print date: 22.05.2023

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier****Trade name**

VE140 Fuel Resistant Vinylester Resin

**UFI**

KP3X-FJHA-R00M-6VEH

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Purpose of use: Raw substance formulas for manufacturing shaped parts from unsaturated polyester / vinyl ester resins.

**Uses advised against**

SU21 Consumer uses: Private households (= general public = consumers)

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Easy Composites Ltd  
 Unit 39, Park Hall Business Village  
 Longton, Stoke on Trent  
 Staffordshire  
 ST3 5XA  
 United Kingdom

**Tel:** +44 (0) 1782 454499**Email:** sales@easycomposites.com**1.4. Emergency telephone number**

Emergency tel: +44 (0) 1782 454499 (office hours only)

**SECTION 2: Hazards identification \*\*\*****2.1. Classification of the substance or mixture****Classification (Regulation (EC) No. 1272/2008)**

Flam. Liq. 3	H226	
Acute Tox. 4	H332	
Skin Irrit. 2	H315	
Eye Irrit. 2	H319	
Repr. 2	H361d	
STOT SE 3	H335	
STOT RE 1	H372	Organs: Ear; Route of exposure: inhalative
Aquatic Chronic 3	H412	

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008  
 For explanation of abbreviations see section 16.

**Labelling according to regulation (EC) No 1272/2008****Labelling according to regulation (EC) No 1272/2008****Hazard pictograms****Signal word**

**VE140 Fuel Resistant Vinylester Resin**

Date revised: 26.01.2023

# 05505904025

Version: 3 / GB

Master No. M-401

Print date: 22.05.2023

Danger

**Hazard statements**

H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure. Ear; Route of exposure: inhalative
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210.9	Keep away from sparks, open flames and other ignition sources. No smoking.
P260.8	Do not breathe vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/ attention.

**Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)**

contains styrene; methacrylic acid

**2.3. Other hazards**

\*\*\*

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Hazardous ingredients****styrene**

CAS No.	100-42-5
EINECS no.	202-851-5
Registration no.	01-2119457861-32-XXXX
Concentration	>= 29 < 50 %
Flam. Liq. 3	H226
Skin Irrit. 2	H315
Acute Tox. 4	H332
Eye Irrit. 2	H319
STOT SE 3	H335
STOT RE 1	H372
Asp. Tox. 1	H304
Repr. 2	H361d
Aquatic Chronic 3	H412

Organs: Ear; Route of exposure: inhalative

cATpE	inhalative, Dust/Mist	1,5	mg/l
ATE	inhalative, Vapors	11,8	mg/l

Additional remarks:

CLP Regulation (EC) No 1272/2008, Annex VI, Note D

**methacrylic acid**

CAS No.	79-41-4
EINECS no.	201-204-4

**VE140 Fuel Resistant Vinylester Resin**

Date revised: 26.01.2023

# 05505904025

Version: 3 / GB

Master No. M-401

Print date: 22.05.2023

Registration no.	01-2119463884-26-0000		
Concentration	>=	1	< 3 %
Acute Tox. 4	H302		
Acute Tox. 4	H312		
Skin Corr. 1A	H314		
	STOT SE 3	H335	>= 1 %
cATpE	oral	500	mg/kg
cATpE	dermal	1.100	mg/kg

Additional remarks:  
 CLP Regulation (EC) No 1272/2008, Annex VI, Note D  
 Complete text of hazard statements in chapter 16

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Adhere to personal protective measures when giving first aid. Remove soiled or soaked clothing immediately, do not allow to dry. If the patient is likely to become unconscious, place and transport in stable sideways position.

**After inhalation**

Remove the casualty into fresh air and keep him calm. Irregular breathing/no breathing: artificial respiration. In the event of symptoms take medical treatment.

**After skin contact**

Wash off immediately with soap and water.

**After eye contact**

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Seek medical advice immediately. Remove contact lenses

**After ingestion**

Rinse mouth thoroughly with water. Summon a doctor immediately. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If individual is drowsy or unconscious place in recovery position (on left side, with head down).

**4.2. Most important symptoms and effects, both acute and delayed**

The following symptoms may occur: Headache, Dizziness, Nausea, Dizziness

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, Dry powder, Carbon dioxide

**Non suitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

In case of combustion evolution of dangerous gases possible. In the event of fire the following can be released: Carbon monoxide (CO); Nitrogen oxides (NOx); dense black smoke

**5.3. Advice for firefighters**

Use self-contained breathing apparatus.

Cool endangered containers with water spray jet. Collect contaminated fire-fighting water separately, must not be discharged into the drains.

VE140 Fuel Resistant Vinylester Resin

Date revised: 26.01.2023

# 05505904025

Version: 3 / GB

Master No. M-401

Print date: 22.05.2023

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin, eyes and clothing. Use personal protective clothing. Keep away sources of ignition. Ensure adequate ventilation. Use breathing apparatus if exposed to vapours/dust/aerosol.

### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. Prevent spread over a wide area (e.g. by containment or oil barriers).

### **6.3. Methods and material for containment and cleaning up**

Pick up with absorbent material (eg sand, kieselgur, acid binder, universal binder, sawdust). When picked up, treat material as prescribed under Section 13 "Disposal".

### **6.4. Reference to other sections**

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid formation of aerosols. Observe the usual precautions for handling chemicals.

Keep away from sources of ignition - No smoking. Take action to prevent static discharges. Vapours can form an explosive mixture with air.

### **7.2. Conditions for safe storage, including any incompatibilities**

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

### **7.3. Specific end use(s)**

No information available

## **SECTION 8: Exposure controls/personal protection**

### **8.1. Control parameters**

#### **Exposure limit values**

##### **methacrylic acid**

List	EH40			
Type	WEL			
Value	72	mg/m <sup>3</sup>	20	ppm(V)
Short term exposure limit	143	mg/m <sup>3</sup>	40	ppm(V)

##### **styrene**

List	EH40			
Type	WEL			
Value	430	mg/m <sup>3</sup>	100	ppm(V)
Short term exposure limit	1080	mg/m <sup>3</sup>	250	ppm(V)

#### **Derived No/Minimal Effect Levels (DNEL/DMEL)**

##### **styrene**

DNEL				
Conditions	Worker	Acute	inhalative	Systemic effects
Concentration	289	mg/m <sup>3</sup>		

DNEL				
Conditions	Worker	Long term	inhalative	Systemic effects

**VE140 Fuel Resistant Vinylester Resin**

Date revised: 26.01.2023

# 05505904025

Version: 3 / GB

Master No. M-401

Print date: 22.05.2023

Concentration	85		mg/m <sup>3</sup>		
DNEL Conditions Concentration	Worker 306	Acute	mg/m <sup>3</sup>	inhalative	Local effects
DNEL Conditions Concentration	Worker 406	Long term	mg/kg/d	dermal	Systemic effects

**8.2. Exposure controls****Appropriate engineering controls**

Use only in well ventilated areas.

Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**General protective and hygiene measures**

Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid contact with skin and eyes. Do not inhale gases/vapours/aerosols. Personal protective equipment must comply with the Regulation (EC) No 2016/425 and the resulting CEN standards.

**Respiratory protection**

If workpiece limits are exceeded, a respiratory protection approved for this particular job must be worn. Short term: filter apparatus, Filter A; Self-contained breathing apparatus. Respiratory protection must comply with DIN EN 136 / DIN EN 140 / DIN EN 143 / DIN EN 149.

**Hand protection**

Chemical resistant gloves

Appropriate Material	Butyl rubber		
Material thickness	0,7	mm	
Breakthrough time	= 30	min	

Hand protection must comply with EN 374.

**Eye protection**

Tightly fitting safety glasses; Eye protection must comply with EN 166.

**Body protection**

Clothing as usual in the chemical industry. Wear protective clothing according to EN 13034: 2005 + A1: 2009.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Form</b>	liquid
<b>Colour</b>	yellow-green
<b>Odour</b>	characteristic
<b>Melting point</b>	
Remarks	Not applicable
<b>Freezing point</b>	
Remarks	Not applicable
<b>Boiling point</b>	
Value	145 °C
Remarks	Information refers to the main component.
<b>Flammability</b>	
No data available	
<b>Explosion limits</b>	

**VE140 Fuel Resistant Vinylester Resin**

Date revised: 26.01.2023

# 05505904025

Version: 3 / GB

Master No. M-401

Print date: 22.05.2023

Lower explosion limit	1,1	to	6,1	%(V)
Remarks	Information refers to the main component.			
<b>Flash point</b>				
Value	33			°C
Method	ISO 3679-B			
<b>Ignition temperature</b>				
Value	490			°C
Remarks	Information refers to the main component.			
<b>Thermal decomposition</b>				
Remarks	No data available			
<b>Self Accelerating Decomposition / Polymerization Temperature (SADT/SAPT)</b>				
Remarks	Not applicable			
<b>pH value</b>				
Remarks	Not applicable			
<b>Solubility in other solvents</b>				
Value	320			mg/l
	25	°C		
Remarks	Information refers to the main component.			
Source	Manufacturer's data			
<b>Octanol/water partition coefficient (log Pow)</b>				
Remarks	No data available			
<b>Vapour pressure</b>				
Value	6,67			hPa
Temperature	20	°C		
Remarks	Information refers to the main component.			
<b>Density</b>				
Value	1,1			g/cm <sup>3</sup>
Temperature	20	°C		
Method	DIN EN ISO 2811			
<b>Vapour density</b>				
Remarks	No data available			
<b>Particle characteristics</b>				
Remarks	Not applicable			

**9.2. Other information****Efflux time**

Value	50	s
Method	DIN EN ISO 2431 - 6 mm	

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

**10.2. Chemical stability**

The product is stable.

**10.3. Possibility of hazardous reactions**

Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4. Conditions to avoid**

Protect from heat and direct sunlight.

**Thermal decomposition**

**VE140 Fuel Resistant Vinylester Resin**

Date revised: 26.01.2023

# 05505904025

Version: 3 / GB

Master No. M-401

Print date: 22.05.2023

Remarks

No data available

**10.5. Incompatible materials**

Reactions with peroxides and other radical components.

**10.6. Hazardous decomposition products**

No hazardous decomposition products known.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity**

ATE	>	10.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)		
Based on available data, the classification criteria are not met.			

**Acute oral toxicity (Components)****styrene**

Species	rat		
LD50	>	5000	mg/kg

**Acute dermal toxicity**

ATE	>	10.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)		
Based on available data, the classification criteria are not met.			

**Acute dermal toxicity (Components)****styrene**

Species	rat		
LD50	>	5000	mg/kg

**Acute inhalational toxicity**

ATE		33,71	mg/l
Administration/Form	Vapors		
Method	calculated value (Regulation (EC) No. 1272/2008)		
ATE		4,29	mg/l
Administration/Form	Dust/Mist		
Method	calculated value (Regulation (EC) No. 1272/2008)		
The classification criteria are met.			

**Acute inhalative toxicity (Components)****styrene**

Species	rat		
LC50		11,8	mg/l
Duration of exposure	4	h	
Administration/Form	Vapors		

**Skin corrosion/irritation**

evaluation	irritant
The classification criteria are met.	

**Serious eye damage/irritation**

evaluation	irritant
The classification criteria are met.	

**Sensitization**

Based on available data, the classification criteria are not met.

**Mutagenicity**

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

VE140 Fuel Resistant Vinylester Resin

Date revised: 26.01.2023

# 05505904025

Version: 3 / GB

Master No. M-401

Print date: 22.05.2023

evaluation Suspected of damaging the unborn child.  
The classification criteria are met.

**Carcinogenicity**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT)****Single exposure**

The classification criteria are met.

evaluation May cause respiratory irritation.

**Repeated exposure**

The classification criteria are met.

evaluation Causes damage to organs through prolonged or repeated exposure

**Specific Target Organ Toxicity (STOT) (Components)****styrene****Repeated exposure**

evaluation Causes damage to organs through prolonged or repeated exposure  
Route of exposure inhalative  
Organs: Ear

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2 Information on other hazards****Endocrine disrupting properties with respect to humans**

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

**Other information**

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness.

**SECTION 12: Ecological information****12.1. Toxicity****Fish toxicity****styrene**

LC/EC/IC50 > 1,0 to 10 mg/l

**Daphnia toxicity****styrene**

Species Daphnia magna  
LC/EC/IC50 > 1,0 to 10 mg/l

**Algae toxicity****styrene**

LC/EC/IC50 > 1,0 to 10 mg/l

**Bacteria toxicity**

No toxicological data are available.

**12.2. Persistence and degradability**

For this subsection there is no ecotoxicological data available on the product as such.

**Biodegradability****styrene**

evaluation Readily biodegradable (according to OECD criteria)

**12.3. Bioaccumulative potential**

For this subsection there is no ecotoxicological data available on the product as such.



---

**VE140 Fuel Resistant Vinylester Resin**

Date revised: 26.01.2023

# 05505904025

Version: 3 / GB

Master No. M-401

Print date: 22.05.2023

---

**Octanol/water partition coefficient (log Pow)**

Remarks

No data available

**12.4. Mobility in soil**

For this subsection there is no ecotoxicological data available on the product as such.

**12.5. Results of PBT and vPvB assessment**

**Evaluation of persistence and bioaccumulation potential**

The product contains no PBT substances

The product contains no vPvB substances.

**12.6. Other adverse effects**

**Endocrine disrupting properties with respect to the environment**

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

**12.7. Other adverse effects**

For this subsection there is no ecotoxicological data available on the product as such.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations for the product**

EWC waste code 07 02 08\* other still bottoms and reaction residues

The listed waste code numbers, according to the European Waste Catalogue (EWC), are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

**Disposal recommendations for packaging**

Packaging that cannot be cleaned should be disposed off as product waste.

**SECTION 14: Transport information \*\*\***

VE140 Fuel Resistant Vinylester Resin



Date revised: 26.01.2023

# 05505904025

Version: 3 / GB

Master No. M-401

Print date: 22.05.2023

	Land transport ADR/RID ***	Marine transport IMDG/GGVSee ***
14.1. UN number	1866	1866
14.2. UN proper shipping name	RESIN SOLUTION	RESIN SOLUTION
14.3. Transport hazard class(es)	3	3
14.4. Packing group	III	III
Label		
14.5. Environmental hazards	-	
Limited Quantity		5 l
Limited Quantity	5 l	
Transport category	3	
Tunnel restriction code	D/E	
Hazard id. no.	30	
EmS		F-E, S-E
Remarks	Viscous product: Transport according to paragraph 2.2.3.1.5 ADR/RID	Transport according to 2.3.2.5 of the IMDG Code

**Information for all modes of transport****14.6. Special precautions for user**

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Other information****14.7 Maritime transport in bulk according to IMO instruments**

Not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Major-accident categories acc. 2012/18/EU**

Category P5c FLAMMABLE LIQUID

**VOC**

VOC (EU) 1,99 %

**VE140 Fuel Resistant Vinylester Resin**

Date revised: 26.01.2023

# 05505904025

Version: 3 / GB

Master No. M-401

Print date: 22.05.2023

**Other information**

The product does not contain substances according to: Candidate List for inclusion in Annex XIV of Regulation (EC) No. 1907/2006 (REACH).

**15.2. Chemical safety assessment**

No information available

**SECTION 16: Other information****Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:**

Flam. Liq. 3	H226	On basis of test data
Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Repr. 2	H361d	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 1	H372	Calculation method
Aquatic Chronic 3	H412	Calculation method

**Hazard statements listed in Chapter 2/3**

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**CLP categories listed in Chapter 2/3**

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1A	Skin corrosion, Category 1A
Skin Irrit. 2	Skin irritation, Category 2
STOT RE 1	Specific target organ toxicity - repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

**Abbreviations**

ATE: Acute Toxicity Estimates  
 CAS: Chemical Abstracts Service  
 cATpE: Converted acute toxicity point estimate  
 EAK: Europäischer Abfallkatalog  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: Very persistent and very bioaccumulative  
 VOC: Volatile Organic Compound

**Supplemental information**

Relevant changes compared with the previous version of the safety data sheet are marked with: \*\*\*  
 This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.

---

**VE140 Fuel Resistant Vinylester Resin**

Date revised: 26.01.2023

# 05505904025

Version: 3 / GB

Master No. M-401

Print date: 22.05.2023

---