



# Xencast PX60 Medium Flexible PU Rubber Part A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Revision date: 02/05/2023  
Version: 7.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : XENCAST® PX60 Medium Flexible Polyurethane Rubber Part A  
Product code : PX60-A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use  
Use of the substance/mixture : Casting compound

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Easy Composites Ltd  
Unit 39, Park Hall Business Village, Stoke on Trent,  
Staffordshire, ST3 5XA. United Kingdom.  
T +44 (0) 1782 454499 (08:00 - 17:30hrs, Mon-Fri) -  
[sales@easycomposites.co.uk](mailto:sales@easycomposites.co.uk) [www.easycomposites.co.uk](http://www.easycomposites.co.uk)

#### 1.4. Emergency telephone number

Emergency number 44 (0) 1782 454499 (08:00 - 17:30hrs, Mon-Fri)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317  
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411  
Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS09

Signal word (CLP)

: Warning

Contains

: A mixture of: 3,5-dimethylthio-2,4-toluenediamine; 3,5-dimethylthio-2,6-toluenediamine

Hazard statements (CLP)

: H317 - May cause an allergic skin reaction.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 - Wear protective gloves, protective clothing, eye protection.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

# Xencast PX60 Medium Flexible PU Rubber Part A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

P362+P364 - Take off contaminated clothing and wash it before reuse.  
P391 - Collect spillage.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
A mixture of: 3,5-dimethylthio-2,4-toluenediamine; 3,5-dimethylthio-2,6-toluenediamine	CAS-No.: 106264-79-3 EC-No.: 403-240-8 EC Index-No.: 612-113-00-8 REACH-no: 01-0000015292-76	1 – 25	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : May cause an allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# Xencast PX60 Medium Flexible PU Rubber Part A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.  
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

No additional information available

##### 8.1.2. Recommended monitoring procedures

No additional information available

##### 8.1.3. Air contaminants formed

No additional information available

##### 8.1.4. DNEL and PNEC

No additional information available

##### 8.1.5. Control banding

No additional information available

# Xencast PX60 Medium Flexible PU Rubber Part A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

**Appropriate engineering controls:**

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

**Personal protective equipment symbol(s):**



##### 8.2.2.1. Eye and face protection

**Eye protection:**

Safety glasses

##### 8.2.2.2. Skin protection

**Skin and body protection:**

Wear suitable protective clothing

**Hand protection:**

Protective gloves

##### 8.2.2.3. Respiratory protection

**Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment

##### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Non flammable.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 800 – 1100 mPa·s (25°C)
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1.02 – 1.07 g/cm <sup>3</sup> (25°C)

# Xencast PX60 Medium Flexible PU Rubber Part A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### A mixture of: 3,5-dimethylthio-2,4-toluenediamine; 3,5-dimethylthio-2,6-toluenediamine (106264-79-3)

LD50 oral rat	1515 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

#### A mixture of: 3,5-dimethylthio-2,4-toluenediamine; 3,5-dimethylthio-2,6-toluenediamine (106264-79-3)

Viscosity, kinematic	7000 mm <sup>2</sup> /s (20°C)
----------------------	--------------------------------

# Xencast PX60 Medium Flexible PU Rubber Part A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.  
Not rapidly degradable

#### A mixture of: 3,5-dimethylthio-2,4-toluenediamine; 3,5-dimethylthio-2,6-toluenediamine (106264-79-3)

LC50 - Fish [1]	7.3 mg/l Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	0.9 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	7.6 mg/l Selenastrum capricornutum
NOEC (chronic)	1.9 mg/l

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

#### A mixture of: 3,5-dimethylthio-2,4-toluenediamine; 3,5-dimethylthio-2,6-toluenediamine (106264-79-3)

BCF - Fish [1]	9.8 – 25
Partition coefficient n-octanol/water (Log Pow)	2.63 (20°C)

### 12.4. Mobility in soil

#### A mixture of: 3,5-dimethylthio-2,4-toluenediamine; 3,5-dimethylthio-2,6-toluenediamine (106264-79-3)

Mobility in soil	4365.16
------------------	---------

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
HP Code : HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.  
HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

# Xencast PX60 Medium Flexible PU Rubber Part A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
Special provision(s) applied : 375	Special provision(s) applied : 969	Special provision(s) applied : A197	Special provision(s) applied : 375	Special provision(s) applied : 375

These substances when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

#### 14.1. UN number or ID number

UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
---------	---------	---------	---------	---------






#### 14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : A mixture of: 3,5-dimethylthio- 2,4-toluenediamine; 3,5- dimethylthio-2,6- toluenediamine)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : A mixture of: 3,5-dimethylthio- 2,4-toluenediamine; 3,5- dimethylthio-2,6- toluenediamine)	Environmentally hazardous substance, liquid, n.o.s. (CONTAINS : A mixture of: 3,5-dimethylthio-2,4- toluenediamine; 3,5- dimethylthio-2,6- toluenediamine)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : A mixture of: 3,5-dimethylthio- 2,4-toluenediamine; 3,5- dimethylthio-2,6- toluenediamine)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : A mixture of: 3,5-dimethylthio- 2,4-toluenediamine; 3,5- dimethylthio-2,6- toluenediamine)
---	---	--	---	---

#### Transport document description

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : A mixture of: 3,5-dimethylthio- 2,4-toluenediamine; 3,5- dimethylthio-2,6- toluenediamine), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : A mixture of: 3,5-dimethylthio- 2,4-toluenediamine; 3,5- dimethylthio-2,6- toluenediamine), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (CONTAINS : A mixture of: 3,5- dimethylthio-2,4- toluenediamine; 3,5- dimethylthio-2,6- toluenediamine), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : A mixture of: 3,5-dimethylthio- 2,4-toluenediamine; 3,5- dimethylthio-2,6- toluenediamine), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : A mixture of: 3,5-dimethylthio- 2,4-toluenediamine; 3,5- dimethylthio-2,6- toluenediamine), 9, III
---	---	--	--	--

#### 14.3. Transport hazard class(es)

9	9	9	9	9
				

#### 14.4. Packing group

III	III	III	III	III
-----	-----	-----	-----	-----

#### 14.5. Environmental hazards

Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
---------------------------------------	--	---------------------------------------	---------------------------------------	---------------------------------------

No supplementary information available

#### 14.6. Special precautions for user

##### Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1

# Xencast PX60 Medium Flexible PU Rubber Part A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	:



Tunnel restriction code (ADR)	: -
EAC code	: •3Z

### Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197, A215
ERG code (IATA)	: 9L

### Inland waterway transport

Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: M6
Special provisions (RID)	: 274, 335, 375, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4



# Xencast PX60 Medium Flexible PU Rubber Part A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Portable tank and bulk container special provisions (RID) : TP1, TP29  
Tank codes for RID tanks (RID) : LGBV  
Transport category (RID) : 3  
Special provisions for carriage – Packages (RID) : W12  
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31  
Colis express (express parcels) (RID) : CE8  
Hazard identification number (RID) : 90

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value

# Xencast PX60 Medium Flexible PU Rubber Part A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Abbreviations and acronyms:

BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

### Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

# Xencast PX60 Medium Flexible PU Rubber Part A

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H411	Toxic to aquatic life with long lasting effects.
Skin Sens. 1	Skin sensitisation, Category 1

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.



# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : XENCAST® PX60 Medium Flexible Polyurethane Rubber Part B  
Product code : PX60-B

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use  
Use of the substance/mixture : Casting compound

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Easy Composites Ltd  
Unit 39, Park Hall Business Village, Stoke on Trent,  
Staffordshire,  
ST3 5XA.  
United Kingdom.  
T +44 (0) 1782 454499 (08:00 - 17:30hrs, Mon-Fri) -  
[sales@easycomposites.com](mailto:sales@easycomposites.com) [www.easycomposites.com](http://www.easycomposites.com)

#### 1.4. Emergency telephone number

Emergency number 44 (0) 1782 454499 (08:00 - 17:30hrs, Mon-Fri)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Respiratory sensitisation, Category 1	H334
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Single exposure, Category 3,	H335
Respiratory tract irritation	
Specific target organ toxicity – Repeated exposure, Category 2	H373
Hazardous to the aquatic environment – Acute Hazard,	H400
Category 1	
Hazardous to the aquatic environment – Chronic Hazard,	H410
Category 1	

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Harmful if inhaled. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Very toxic to aquatic life with long lasting effects.



# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

Extra phrases

- : Danger
- : Prepolymer based on aromatic isocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate; 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate
- : H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H332 - Harmful if inhaled.  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 - May cause respiratory irritation.  
H351 - Suspected of causing cancer.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H410 - Very toxic to aquatic life with long lasting effects.
- : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 - Wear protective gloves, protective clothing, eye protection.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor.  
P391 - Collect spillage.
- : As from 24 August 2023 adequate training is required before industrial or professional use.

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bis(isopropyl)naphthalene [mixture of isomers]	CAS-No.: 38640-62-9 EC-No.: 254-052-6 REACH-no: 01-2119565150-48	25 – 50	Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Prepolymer based on aromatic isocyanate	CAS-No.: 99784-49-3	25 – 50	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335 STOT RE 2, H373



# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate substance with national workplace exposure limit(s) (GB)	CAS-No.: 5873-54-1 EC-No.: 227-534-9 EC Index-No.: 615-005-00-9 REACH-no: 01-2119480143-45	1 – 25	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate substance with national workplace exposure limit(s) (GB)	CAS-No.: 101-68-8 EC-No.: 202-966-0 EC Index-No.: 615-005-00-9 REACH-no: 01-2119457014-47	1 – 25	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

### Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate	CAS-No.: 5873-54-1 EC-No.: 227-534-9 EC Index-No.: 615-005-00-9 REACH-no: 01-2119480143-45	(0.1 ≤ C ≤ 100) Resp. Sens. 1, H334 (5 ≤ C ≤ 100) Eye Irrit. 2, H319 (5 ≤ C ≤ 100) Skin Irrit. 2, H315 (5 ≤ C ≤ 100) STOT SE 3, H335
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate	CAS-No.: 101-68-8 EC-No.: 202-966-0 EC Index-No.: 615-005-00-9 REACH-no: 01-2119457014-47	(0.1 ≤ C ≤ 100) Resp. Sens. 1, H334 (5 ≤ C ≤ 100) Eye Irrit. 2, H319 (5 ≤ C ≤ 100) Skin Irrit. 2, H315 (5 ≤ C ≤ 100) STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.



# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

##### o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate (5873-54-1)

##### United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA)	0.02 mg/m <sup>3</sup>
WEL STEL (OEL STEL)	0.07 mg/m <sup>3</sup>

##### 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)

##### United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA)	0.02 mg/m <sup>3</sup>
WEL STEL (OEL STEL)	0.07 mg/m <sup>3</sup>

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment symbol(s):



##### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

##### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

##### 8.2.2.3. Respiratory protection

##### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

##### 8.2.2.4. Thermal hazards

No additional information available





# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 100 – 140 mPa·s (25°C)
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1 – 1.05 g/cm <sup>3</sup> (25°C)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available



# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

#### Alchemix PU 3546B

ATE CLP (dust,mist)	3.003 mg/l/4h
---------------------	---------------

#### Prepolymer based on aromatic isocyanate (99784-49-3)

LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 9400 mg/kg

#### o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate (5873-54-1)

LD50 oral rat	> 2000 mg/kg Source: ECHA
LD50 dermal rabbit	> 9400 mg/kg Source: ECHA

#### 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)

LD50 oral rat	> 2000 mg/kg Source: ECHA
LD50 dermal rabbit	> 9400 mg/kg Source: ECHA

#### Bis(isopropyl)naphthalene [mixture of isomers] (38640-62-9)

LD50 oral rat	> 4000 mg/kg
LD50 dermal rat	> 4500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:
LC50 Inhalation - Rat	> 5.64 mg/kg Source: IUCLID

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Suspected of causing cancer.

#### 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified  
STOT-single exposure : May cause respiratory irritation.

#### Prepolymer based on aromatic isocyanate (99784-49-3)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

#### o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate (5873-54-1)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

#### 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.



# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

### Prepolymer based on aromatic isocyanate (99784-49-3)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

### o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate (5873-54-1)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

### 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard : Not classified

### Bis(isopropyl)naphthalene [mixture of isomers] (38640-62-9)

Viscosity, kinematic	6.25 mm <sup>2</sup> /s (40°C)
----------------------	--------------------------------

Hydrocarbon	Yes
-------------	-----

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.  
Hazardous to the aquatic environment, long-term (chronic) : Very toxic to aquatic life with long lasting effects.

### o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate (5873-54-1)

LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
-----------------	--

NOEC (chronic)	≥ 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC chronic crustacea	> 10 mg/l Daphnia magna (Water flea)
------------------------	--------------------------------------

### 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)

NOEC (chronic)	≥ 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

### Bis(isopropyl)naphthalene [mixture of isomers] (38640-62-9)

LC50 - Fish [1]	> 0.5 mg/l Test organisms (species): Leuciscus idus
-----------------	---

EC50 - Crustacea [1]	> 0.16 mg/l Test organisms (species): Daphnia magna
----------------------	---

NOEC chronic crustacea	0.013 mg/l daphnia
------------------------	--------------------

### 12.2. Persistence and degradability

#### Alchemix PU 3546B

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### Prepolymer based on aromatic isocyanate (99784-49-3)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate (5873-54-1)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------



# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

### Bis(isopropyl)naphthalene [mixture of isomers] (38640-62-9)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

### 12.3. Bioaccumulative potential

#### o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate (5873-54-1)

Partition coefficient n-octanol/water (Log Pow)	4.51 Source: ECHA
---	-------------------

#### 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)

Partition coefficient n-octanol/water (Log Pow)	4.51 Source: ECHA
---	-------------------

### Bis(isopropyl)naphthalene [mixture of isomers] (38640-62-9)

Bioconcentration factor (BCF REACH)	> 500
Partition coefficient n-octanol/water (Log Pow)	> 4 Source: IUCLID

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW, EC 2000/532)	: 08 05 01* - waste isocyanates
HP Code	: HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure. HP7 - "Carcinogenic:" waste which induces cancer or increases its incidence HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID






ADR	IMDG	IATA	ADN	RID
Special provision(s) applied : 375	Special provision(s) applied : 969	Special provision(s) applied : A197	Special provision(s) applied : 375	Special provision(s) applied : 375



# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

ADR	IMDG	IATA	ADN	RID
These substances when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.				
<b>14.1. UN number or ID number</b>				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
<b>14.2. UN proper shipping name</b>				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : Bis(isopropyl)naphthalene [mixture of isomers])	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : Bis(isopropyl)naphthalene [mixture of isomers])	Environmentally hazardous substance, liquid, n.o.s. (CONTAINS : Bis(isopropyl)naphthalene [mixture of isomers])	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : Bis(isopropyl)naphthalene [mixture of isomers])	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : Bis(isopropyl)naphthalene [mixture of isomers])
<b>Transport document description</b>				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : Bis(isopropyl)naphthalene [mixture of isomers]), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : Bis(isopropyl)naphthalene [mixture of isomers]), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (CONTAINS : Bis(isopropyl)naphthalene [mixture of isomers]), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : Bis(isopropyl)naphthalene [mixture of isomers]), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS : Bis(isopropyl)naphthalene [mixture of isomers]), 9, III
<b>14.3. Transport hazard class(es)</b>				
9	9	9	9	9
				
<b>14.4. Packing group</b>				
III	III	III	III	III
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12



# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

Special provisions for carriage - Loading, unloading and handling (ADR) : CV13  
Hazard identification number (Kemler No.) : 90  
Orange plates :



Tunnel restriction code (ADR) : -  
EAC code : •3Z

### Transport by sea

Special provisions (IMDG) : 274, 335, 969  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : LP01, P001  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1, TP29  
EmS-No. (Fire) : F-A  
EmS-No. (Spillage) : S-F  
Stowage category (IMDG) : A

### Air transport

PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y964  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 964  
PCA max net quantity (IATA) : 450L  
CAO packing instructions (IATA) : 964  
CAO max net quantity (IATA) : 450L  
Special provisions (IATA) : A97, A158, A197, A215  
ERG code (IATA) : 9L

### Inland waterway transport

Classification code (ADN) : M6  
Special provisions (ADN) : 274, 335, 375, 601  
Limited quantities (ADN) : 5 L  
Excepted quantities (ADN) : E1  
Carriage permitted (ADN) : T  
Equipment required (ADN) : PP  
Number of blue cones/lights (ADN) : 0

### Rail transport

Classification code (RID) : M6  
Special provisions (RID) : 274, 335, 375, 601  
Limited quantities (RID) : 5L  
Excepted quantities (RID) : E1  
Packing instructions (RID) : P001, IBC03, LP01, R001  
Special packing provisions (RID) : PP1  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T4  
Portable tank and bulk container special provisions (RID) : TP1, TP29  
Tank codes for RID tanks (RID) : LGBV  
Transport category (RID) : 3  
Special provisions for carriage – Packages (RID) : W12  
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31  
Colis express (express parcels) (RID) : CE8  
Hazard identification number (RID) : 90



# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

##### EU restriction list (REACH Annex XVII)

Reference code	Applicable on	Entry title or description
56.	o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate ; 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate	Methylenediphenyl diisocyanate (MDI)
56(a)	4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 4,4'-Methylenediphenyl diisocyanate
56(b)	o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 2,4'-Methylenediphenyl diisocyanate
74.	Prepolymer based on aromatic isocyanate ; o-(p-isocyanatobenzyl)phenyl isocyanate; diphenylmethane-2,4'-diisocyanate ; 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate	Diisocyanates, $O = C=N-R-N = C=O$ , with R an aliphatic or aromatic hydrocarbon unit of unspecified length

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)



# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

### Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail





# Xencast PX60 Medium Flexible PU Rubber Part B

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Revision date: 12/06/2024 Version: 8.0

### Abbreviations and acronyms:

SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

### Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.