


Kevlar Cloth



Handling & Storage

Kevlar is sensitive to UV light so we recommend storing in a dark place to minimise the chance of UV degredation.

Product Description

High quality 300gsm woven Kevlar® fabric reinforcement using genuine Dupont® Kevlar® yarn in a 2x2 twill weave for good drapabily. This fabric is 1m (1000mm) wide and sold by the linear metre.

This high performance aramid cloth can be used on its own to make panels with maximum impact strength or used in combination to add impact strength to carbon or glass fibre laminates in applications such as motorsport panels, canoes, kayaks etc.

This Kevlar® brand heavyweight 300g kevlar cloth 2/2 twill weave can be used on its own or in conjunction with other reinforcement fabrics (such as carbon fibre) to achieve a very strong and impact resilient composite.

Kevlar® provides very high resistance to impact and abrasion and is much more resilient to fracture separation than other reinforcements (including carbon fibre).

Twill Kevlar® cloth can be laminated in just the same way as carbon fibre. It is suitable for use in wet-lay, vacuum bagging or resin infusion. For maximum performance Kevlar® should always be laminated with Epoxy resin.

Specification

Property	Units	Value
Material	-	Kevlar 49
Colour	-	Yellow
Format	-	Woven Fabric
Weave Type	-	2x2 Twill
Width	mm	1000
Areal Weight	g/cm²	300
Thickness	mm	0.47
Consolidated Thickness	mm	0.40
Ends	/cm	4.75
Picks	/cm	4.75
Tensile Strength	mPa	3000
Tensile Modulos	gPa	112.4
Poissons Ratio	-	0.36
Elongation at Break	%	2.4
Maximum Service Temperature In Air	°C	149 - 177
Density	g/cm³	1.44

Disclaimer

This data is not to be used for specifications. Values listed are for typical properties and should not be considered minimum or maximum.

Our technical advice, whether verbal or in writing, is given in good faith but Easy Composites Ltd gives no warranty; express or implied, and all products are sold upon condition that purchasers will make their own tests to determine the quality and suitability of the product for their particular application and circumstances.

Easy Composites Ltd shall be in no way responsible for the proper use and service of the product, nor for the safeguarding of personnel or property, all of which is the duty of the user. Any information or suggestions are without warranty of any kind and purchasers are solely responsible for any loss arising from the use of such information or suggestions. No information or suggestions given by us shall be deemed to be a recommendation to use any product in conflict with any existing patent rights. Before using any of our products, users should familiarise themselves with the relevant technical and safety datasheets provided by Easy Composites Ltd.

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.