



# West & Senior Limited

Milltown Street • Radcliffe • Manchester • M26 1WE • United Kingdom

Tel +44 (0) 161 724 7131 • Fax +44 (0) 161 724 9519

<http://www.westsenior.co.uk> • [info@westsenior.co.uk](mailto:info@westsenior.co.uk)

## SAFETY DATA SHEET PEPU FASCOL DUST GREY PIGMENT

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** PEPU FASCOL DUST GREY PIGMENT

**Product number** WS26183A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Colouring of PU systems for CASE applications.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** WEST AND SENIOR LIMITED.  
MILLTOWN STREET  
RADCLIFFE  
MANCHESTER. M26 1WE.  
TEL + 44 01617247131  
FAX + 44 01617249519  
[info@westsenior.co.uk](mailto:info@westsenior.co.uk)

#### 1.4. Emergency telephone number

**Emergency telephone** 24 HOUR EMERGENCY TELEPHONE NUMBER : +44 7379825059

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (SI 2019 No. 720)

**Physical hazards** Not Classified

**Health hazards** Not Classified

**Environmental hazards** Not Classified

**Environmental** The product is not expected to be hazardous to the environment.

#### 2.2. Label elements

**Hazard statements** NC Not Classified

**Supplemental label information** EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

## PEPU FASCOL DUST GREY PIGMENT

|   |                      |
|---|----------------------|
| <b>TITANIUM DIOXIDE</b>                 | <b>30-60%</b>        |
| CAS number: 13463-67-7                  | EC number: 236-675-5 |
| <b>Classification</b><br>Not Classified |                      |
| <b>Natural Calcium Carbonate</b>        | <b>1-5%</b>          |
| CAS number: 1317-65-3                   | EC number: 215-279-6 |
| <b>Classification</b><br>Not Classified |                      |
| <b>C.I. PIGMENT YELLOW 42</b>           | <b>1-5%</b>          |
| CAS number: 51274-00-1                  | EC number: 257-098-5 |
| <b>Classification</b><br>Not Classified |                      |

The full text for all hazard statements is displayed in Section 16.

**Composition comments** This mixture contains  $\geq 1\%$  Titanium Dioxide (CAS 13463-67-7) The Annex VI classification of Titanium Dioxide does not apply to this mixture according to its Note 10. No other disclosure required under the latest EC Directives

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

|                            |   |
|----------------------------|---|
| <b>General information</b> | No specific recommendations. If in doubt, get medical attention promptly.   |
| <b>Inhalation</b>          | Move affected person to fresh air at once. Get medical attention if any discomfort continues.   |
| <b>Ingestion</b>           | Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues. |
| <b>Skin contact</b>        | Remove affected person from source of contamination. Get medical attention if irritation persists after washing.  |
| <b>Eye contact</b>         | Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.     |

#### 4.2. Most important symptoms and effects, both acute and delayed

**General information** No specific symptoms noted.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** No specific symptoms noted. No specific antedote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with the following media: Alcohol-resistant foam. Water spray, fog or mist. Carbon dioxide (CO<sub>2</sub>). Small fires: Dry chemicals, soda ash, lime.

## PEPU FASCOL DUST GREY PIGMENT

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

**Hazardous combustion products** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Fire or high temperatures create: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### 5.3. Advice for firefighters

**Protective actions during firefighting** Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discolouration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contaminated may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this SDS.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Isolate area. Keep unnecessary and unprotected personnel from entering the area. Spilled material may cause a slipping hazard.

### 6.2. Environmental precautions

**Environmental precautions** Do not discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Stop leak if safe to do so. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container. Keep away from food, drink and animal feeding stuffs. Store at temperatures between 15°C and 35°C.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## PEPU FASCOL DUST GREY PIGMENT

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### **TITANIUM DIOXIDE**

EH40 WEL, Time Weighted Average (TWA):, Inhalable dust. 10 mg/m<sup>3</sup>, 8 h

EH40 WEL, Time Weighted Average (TWA):, Respirable dust. 4 mg/m<sup>3</sup>, 8 h

##### **Natural Calcium Carbonate**

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> respirable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> inhalable dust

##### **C.I. PIGMENT YELLOW 42**

Long-term exposure limit (8-hour TWA): 5 mg/m<sup>3</sup>, Iron. fume

Short-term exposure limit (15-minute): 10 mg/m<sup>3</sup>, Iron. fume

##### **RED OXIDE C.I. PIGMENT RED 101**

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> respirable dust

Long-term exposure limit (8-hour TWA): WEL 5 mg/m<sup>3</sup> fume

Short-term exposure limit (15-minute): WEL 10 mg/m<sup>3</sup> fume

as Fe

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> inhalable dust

WEL = Workplace Exposure Limit.

**Ingredient comments**                      No exposure limits known for ingredient(s).

#### TITANIUM DIOXIDE (CAS: 13463-67-7)

|             |   |
|-------------|---|
| <b>DNEL</b> | Workers - Inhalation; Long term local effects: 10 mg/m <sup>3</sup><br>Professional - Inhalation; Long term local effects: 10 mg/m <sup>3</sup><br>Consumer - Oral; Long term systemic effects: 700 mg/kg/day |
| <b>PNEC</b> | marine water; 0.0184 mg/l<br>Fresh water; 0.184 mg/l<br>Intermittent release; 0.193 mg/l<br>STP; 100 mg/l<br>Sediment, marine water; 100 mg/kg<br>Sediment, Fresh water; 1000 mg/kg<br>Soil; 100 mg/kg        |

#### POLYETHER POLYOL (CAS: 9082-00-2)

**Ingredient comments**                      No exposure limits known for ingredient(s).

#### C.I. PIGMENT BLACK 11 (CAS: 1317-61-9)

**Ingredient comments**                      No exposure limits known for ingredient(s).

**DNEL**    Workers - Inhalation; Long term systemic effects: 10 mg/m<sup>3</sup>  
Workers - Inhalation; Long term local effects: 10 mg/m<sup>3</sup>

#### C.I. PIGMENT YELLOW 42 (CAS: 51274-00-1)

**DNEL**    Workers - Inhalation; Long term local effects: 10 mg/cm<sup>2</sup>

#### RED OXIDE C.I. PIGMENT RED 101 (CAS: 1309-37-1)

## PEPU FASCOL DUST GREY PIGMENT

**DNEL** Workers - Inhalation; Long term systemic effects: 10 mg/m<sup>3</sup>  
Workers - Inhalation; Long term local effects: 10 mg/m<sup>3</sup>

### Trimethylolpropane (CAS: 77-99-6)

**DNEL** Workers - Inhalation; Long term systemic effects: 3.3 mg/m<sup>3</sup>  
Workers - Dermal; Long term systemic effects: 0.94 mg/kg  
Consumer - Inhalation; Long term systemic effects: 0.58 mg/m<sup>3</sup>  
Consumer - Dermal; Long term systemic effects: 0.34 mg/kg  
Consumer - Oral; Long term systemic effects: 0.34 mg/kg

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

No specific ventilation requirements.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

### Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact. Wear apron or protective clothing in case of contact.

### Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

### Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|  |                                     |
|--|-------------------------------------|
| <b>Appearance</b>                      | Coloured paste.                     |
| <b>Colour</b>                          | Variable                            |
| <b>Odour</b>                           | Sweetish.                           |
| <b>Odour threshold</b>                 | No information available.           |
| <b>pH</b>                              | Not applicable.                     |
| <b>Melting point</b>                   | No information available.           |
| <b>Initial boiling point and range</b> | >100°C @ 760 mm Hg Estimated value. |
| <b>Flash point</b>                     | >182°C Closed cup.                  |
| <b>Evaporation rate</b>                | No information available.           |
| <b>Evaporation factor</b>              | No information available.           |

## PEPU FASCOL DUST GREY PIGMENT

|   |                                 |
|---|---------------------------------|
| <b>Flammability (solid, gas)</b>                    | Not applicable.                 |
| <b>Upper/lower flammability or explosive limits</b> | No information available.       |
| <b>Other flammability</b>                           | No information available.       |
| <b>Vapour pressure</b>                              | No information available.       |
| <b>Vapour density</b>                               | No information available.       |
| <b>Relative density</b>                             | No information available.       |
| <b>Bulk density</b>                                 | No information available.       |
| <b>Solubility(ies)</b>                              | No information available.       |
| <b>Partition coefficient</b>                        | No information available.       |
| <b>Auto-ignition temperature</b>                    | No information available.       |
| <b>Decomposition Temperature</b>                    | No information available.       |
| <b>Viscosity</b>                                    | No information available.       |
| <b>Explosive properties</b>                         | Not considered to be explosive. |
| <b>Explosive under the influence of a flame</b>     | No                              |
| <b>Oxidising properties</b>                         | No                              |
| <b>Comments</b>                                     | None                            |

### 9.2. Other information

**Other information** No information required.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Stable at normal ambient temperatures and when used as recommended.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Will not polymerise.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid excessive heat for prolonged periods of time. Avoid contact with strong oxidising agents. Avoid contact with the following materials: Water, moisture.

### 10.5. Incompatible materials

**Materials to avoid** Strong oxidising agents. Strong acids. The reaction of polyols and isocyanates generates heat. Isocyanates.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Decomposition products depend upon temperature, air supply and the presence of other materials. Thermal decomposition or combustion products may include the following substances: Aldehydes. Ketones. Acids - organic. Polymer fragments.

## PEPU FASCOL DUST GREY PIGMENT

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**Toxicological effects** Not classified.

**Acute and chronic health hazards** No specific health hazards known.

### SECTION 12: Ecological information

**Ecotoxicity** Not regarded as dangerous for the environment.

#### 12.1. Toxicity

**Toxicity** Not considered toxic to fish.

#### 12.2. Persistence and degradability

**Persistence and degradability** Not expected to be readily biodegradable.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** The product is not bioaccumulating.

**Partition coefficient** No information available.

#### 12.4. Mobility in soil

**Mobility** No data available.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** Not applicable.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### SECTION 14: Transport information

**Rail transport notes** Not classified.

**Sea transport notes** Not classified.

**Air transport notes** Not classified.

#### 14.1. UN number

Not applicable.

#### 14.2. UN proper shipping name

Not applicable.

#### 14.3. Transport hazard class(es)

Not applicable.

#### 14.4. Packing group

## PEPU FASCOL DUST GREY PIGMENT

Not applicable.

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

Not applicable.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

|                             |   |
|-----------------------------|---|
| <b>National regulations</b> | Control of Substances Hazardous to Health Regulations 2002 (as amended).  |
| <b>EU legislation</b>       | Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. |
| <b>Guidance</b>             | A guide to local exhaust ventilation (LEV) HSG258 (as ammended)<br>Workplace Exposure Limits EH40.  |

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

|                        |            |
|------------------------|------------|
| <b>Revision date</b>   | 18/04/2023 |
| <b>Revision</b>        | 5          |
| <b>Supersedes date</b> | 23/03/2017 |

The information contained within this document is presented in good faith and is believed to be correct. West and Senior Limited makes no representation as to the accuracy and/or completeness of this information. This information is issued on the condition that the user will determine the safety and suitability of products for their purposes prior to use. All technical details and values presented are deemed typical and do not constitute a delivery specification.